

MEMORANDUM

TO: Matt Morrison, Tracey Piccone, Tom Kosier, Jose Otero, Dewey Worth
FROM: Gary Goforth
DATE: October 17, 2006
SUBJECT: Preliminary Sizing Analysis of the Proposed EAASR STA - Final Draft

1.0 EXECUTIVE SUMMARY

The South Florida Water Management District (SFWMD) in partnership with the U. S. Army Corps of Engineers (USACE) is developing a Project Implementation Report for the Everglades Agricultural Area Storage Reservoir (EAASR – see **Figure 1**). In order to achieve appropriate water quality in environmental deliveries to the Everglades Protection Area (EPA), the Project Development Team (PDT) is conducting a feasibility-level evaluation of a stormwater treatment area (STA). Additional background information is contained in a *Conceptual-level Sizing Analysis of the Proposed EAASR STA* (Goforth 2006). Simulated flows from the EAA5 scenario of the South Florida Water Management Model (SFWMM) were used to develop a 35-year period of daily reservoir and STA inflow for use in water quality modeling. In recognition of the increased TP concentrations in Lake Okeechobee deliveries to the EAA over the past two water years, the monthly TP concentrations in lake deliveries developed in the EAA Regional Feasibility Study were adjusted to achieve flow-weighted mean concentrations of 100, 150 and 200 ppb at the inflow to the reservoirs and STAs. In recognition of the increased TP concentrations in EAA runoff over the past two water years, the 1995-2004 period of record developed in the EAA Regional Feasibility Study was adjusted. The resulting 12-year period of record monthly TP concentrations were used to develop daily TP inflows to the reservoirs and STAs. The previous *Conceptual Analysis* identified the target long-term average flow-weighted mean TP outflow concentration for the STAs as the most sensitive parameter in sizing the proposed STA. For the purpose of this feasibility-level analysis, three targets were used: 12 ppb, 15 ppb and 19 ppb; the State’s regulatory process will determine the ultimate effluent limitation. Preliminary estimates of the effective treatment area required to achieve the target outflow concentration at the various Lake delivery concentrations were established using the DMSTA model (Walker and Kadlec 2005), and are summarized in **Table 1**. An appropriate uncertainty band should be used around the estimates in **Table 1**, consistent with the present level of uncertainty in the PIR process, i.e., 20%. An evaluation of the potential phosphorus removal effects of lower calcium concentrations in Lake deliveries relative to EAA runoff indicated the possible additional need for 2,500-3,500 acres to meet the same outflow targets.


Table 1. Preliminary Estimates of EAASR STA Size (acres)

Lake Deliveries TP (ppb)	Target Outflow TP Concentration (ppb)		
	12	15	19
100	10,800	6,200	1,900
150	14,600	9,600	5,200
200	17,600	12,500	8,000

Note: Long-term outflow concentrations below 15 ppb have not been demonstrated for treatment wetlands constructed on prior agricultural soils. Additional uncertainty exists in flow estimates, reservoir operations and regional water management.



Figure 1.



2.0 STA SIZING STRATEGY

An initial strategy for sizing the proposed STA was developed by the EAASR PDT and refined in the *Conceptual Analysis* (Goforth 2006). The strategy below was used in developing the feasibility-level estimates of effective treatment area for the proposed STA.

1. Determine the source and initial estimate of the volume of “new water” to be treated by the proposed STA. An initial estimate of the inflow volume will be obtained using SFWMM data by comparing the “With Project” and “Without Project” conditions. These volumes will be derived from SFWMM variables demonstrating 1) reservoir inputs from the Lake Okeechobee, 2) reservoir inputs from EAA basin runoff, 3) deliveries to the environment [currently represented in the SFWMM by deliveries to STA-3/4 and bypass], and 4) consideration of phosphorus performance of the integrated project components. The ultimate difference between the “With Project” and “Without Project” conditions will be greater than the simple numerical difference between the simulated net flows, in that redistribution of flows will likely be necessary in order to achieve the appropriate phosphorus water quality levels. Depending on the inflow source, the phosphorus concentration will vary, and to the



Final Draft - EAASR STA Preliminary Sizing Analysis

extent that the “With Project” and “Without Project” simulations result in different volumes and sources, the associated phosphorus loads to the reservoirs and STAs will differ. An iterative process of hydrologic and water quality modeling will likely be required to finalize the “With Project” conditions and determine the ultimate inflow volume and associated phosphorus load to be treated in the new STA. During this feasibility-level analysis, the model run EAA5 was used to initially estimate flows for the “With Project” condition. Revisions to EAA5 are anticipated that will incorporate the preliminary size of the new STA. Operational modifications will be made to meet the long-term inflow targets for the STAs, as well as all other assumptions, constraints, and operational intent as part of the Next Added Increment (NAI) simulation. Flows from this new NAI will be checked with DMSTA to ensure the treatment capacities of STA 2, Compartment B, and STA-3/4 are not exceeded, and to finalize the size of the new STA. The “Without Project” simulation is not yet complete, and will include the features associated with Alternative 1 of the EAA Regional Feasibility Study (including Compartment B), the Tentatively Selected Plan for the Lake Okeechobee Regulations Schedule Study, and the Combined Structural & Operations Plan for delivery of water to the Everglades national Park. In the interim, the 2050B3EAA simulation results are placeholders for the “Without Project” condition. The estimated size of the STA will need to be updated later when final simulations are available.

2. Forecast the phosphorus concentration of Lake Okeechobee releases and basin runoff delivered to the reservoir and STA-3/4 under the “With Project” and “Without Project” conditions. These forecasts will be based on recent studies.
3. Estimate the phosphorus settling rate and other treatment characteristics of the EAASR, STA-3/4 and the proposed STA based on recent studies.
4. Estimate the anticipated volume and phosphorus load of water delivered to the proposed STA after consideration of STA-3/4 treatment capacity. The volume of water re-directed to the new STA will vary depending upon the flows and treatment capacity of STA-3/4, as that treatment area must also achieve the appropriate water quality for deliveries to the EPA.
5. Estimate the effective treatment area required for STA-3/4 under the “Without Project” condition and the combined treatment area for the “With Project” condition to achieve the target outflow concentrations. The difference between the “With Project” area and the “Without Project” area would be the initial estimate of the incremental treatment area requirement associated with the EAASR.
6. Conduct a sensitivity analysis to determine the influence of critical design parameters on the estimated effective treatment area of the proposed STA. An appropriate range of values will be established based on recent studies, and where recent data are not available, upon best professional judgment.



3.0 CRITICAL ASSUMPTIONS

Target Outflow TP Concentration. The previous *Conceptual Analysis* identified the target long-term average flow-weighted mean TP outflow concentration for the STAs as the most sensitive parameter in sizing the proposed STA (Goforth 2006). Florida has adopted a water quality standard for Total Phosphorus (TP) for the Everglades, with a numeric criterion of a long-term geometric mean of 10 ppb (62-302.540, F.A.C.). The water quality treatment goal for the new STA and STA-3/4 is to achieve compliance with the new TP water quality standard. The Florida Department of Environmental Protection (FDEP) has not yet established a Water-Quality Based Effluent Limitation (62.650 F.A.C.) for discharges into the Everglades. FDEP will establish the effluent limitation in accordance with the State process, however, the results will not be available in time for this analysis. To assist in estimating a range of STA sizes for this feasibility-level analysis, a range of long-term outflow flow-weighted mean TP concentration targets was used. A lower value of 12 ppb was selected¹. A second target of 15 ppb was identified as the lowest flow-weighted mean concentration observed in the calibration data set for a large-scale treatment cell constructed on prior agricultural land. A third target of 19 ppb will be used as an upper bound on the sensitivity analysis. The target concentrations used in this analysis are long-term flow-weighted means. The use of target outflow concentrations in this analysis does not in any way pre-ordain what the ultimate discharge limit will be.

Lake Okeechobee Concentration. The previous *Conceptual Analysis* identified the TP concentration in Lake Okeechobee deliveries to the reservoirs and STAs as the second most sensitive parameter in sizing the proposed STA (Goforth 2006). As a result of the compounding negative effects of the 2005-2006 hurricanes and the positive benefits of the Lake Okeechobee Protection Plan and associated CERP projects implementation, it is difficult to predict with certainty future Lake TP concentrations. In light of the uncertainty of the long-term TP concentrations for Lake Okeechobee deliveries to the reservoirs and STAs, a range of 100 ppb, 150 ppb and 200 ppb was used in the analysis.

Other assumptions. A summary of the critical assumptions incorporated into this analysis is attached as **Appendix 1**. Additional modeling assumptions are discussed below.

¹ An annual flow-weighted mean outflow concentration of 11 ppb was observed for STA-6 during WY2004, and 13 ppb was observed for STA-3/4 during WY2005 (Pietro et al. 2006).



4.0 ANALYTICAL APPROACH FOR ESTIMATING EFFECTIVE TREATMENT AREA

The primary method for estimating the total effective treatment area required to achieve the target outflow concentrations was Version 2 of DMSTA (Walker and Kadlec 2005). To assist in the iterative solution of the treatment area size, a steady-state design model (SSDM) was used; details of the SSDM are provided in the initial *Conceptual Analysis* (Goforth 2006). Using the SSDM with K values derived directly from STA performance yields overly optimistic performance forecasts relative to DMSTA, a reflection of DMSTA's ability to consider pulsed flows and atmospheric deposition, which become more important as the target outflow concentrations decrease. For the purpose of this analysis, the value of K for the SSDM was adjusted, i.e., decreased, to match the STA performance projection from similar DMSTA scenarios.

5.0 INFLOW VOLUMES AND LOADS

An estimate of the reservoir and STA inflows and phosphorus loads were developed by utilizing the following assumptions.

1. Daily flows from the EAA5 scenario of the South Florida Water Management Model (SFWMM) were used to develop daily time series for the DMSTA simulations. **Appendix 2** contains the flow terms and distributions for EAA5. Daily rainfall, evapotranspiration, and reservoir depths from the EAA5 scenario were also used in the DMSTA simulation. A summary of the SFWMM EAA5 scenario is presented in **Table 2**. Depending on the inflow source, the phosphorus concentration will vary, and to the extent that different SFWMM simulations result in different volumes and sources, the associated phosphorus loads to the reservoirs and STAs will differ. An iterative process of hydrologic and water quality modeling will likely be required to finalize the "With Project" conditions and determine the ultimate inflow volume and associated phosphorus load to be treated in the new STA.
2. Consistent with the EAA Regional Feasibility Study (ADA/Burns and McDonnell 2005), the only STAs that will be used to capture and treat Lake Okeechobee regulatory releases are STA-3/4 and the new STA; no other STA will receive regulatory releases and water supply deliveries intended for downstream receiving waters.
3. All runoff from extreme meteorological events simulated in the 1995-2000 period of simulation will be treated, as opposed to being diverted into the WCAs without treatment.
4. EAA irrigation water releases do not need to be treated to Everglades water quality standards prior to discharge back to the EAA.
5. The new STA, working in conjunction with STA-3/4, will treat the volumes of water anticipated to be discharged into the Everglades associated with the EAASR. In other words, the combined areas of STA-3/4 and the new STA are to be used to meet the treatment goals of the project.



Final Draft - EAASR STA Preliminary Sizing Analysis

6. Compartment B will be used primarily to capture and treat water from the S-6 and S-5A basins, and will not be used to capture and treat any Lake Okeechobee releases, or EAASR releases conveyed through the North New River Canal.
7. In recognition of the increased TP concentrations in EAA runoff over the past two water years, the 1995-2004 period of record used by ADA/B&M in the EAA RFS was adjusted to include WY2005 and 2006. The resulting 2-year period of record monthly TP concentrations were used to develop daily time series of TP inflows to the reservoirs and STAs. **Tables 3 and 4** present a summary of the monthly TP concentrations. Additional details are provided in **Appendix 3**.
8. Phosphorus concentrations developed during the EAA Regional Feasibility Study can be used for Ch. 298 District runoff and the C-139 Basin inflows to the EAASR.
9. To reflect the seasonal variations exhibited by Lake Okeechobee deliveries, monthly concentrations were developed. These monthly concentrations were adjusted for each Lake TP level (100 ppb, 150 ppb, and 200 ppb) and further adjusted for each reservoir and STA inflow time series to ensure that the desired flow-weighted mean inflow TP concentrations were achieved at the inflow points. Resulting monthly concentrations are presented in **Table 5**.
10. A May 1 – April 30 Water Year was used in these analyses.
11. A portion of the water supply deliveries for downstream areas will be diverted untreated around STA-3/4 and the new STA. The SFWMM simulation estimated the volume diverted as approximately 33,465 AF/yr. The majority of this (20,553 AF/yr) was diverted to the Seminole Big Cypress Reservation through the L-4 Borrow Canal and L-3 Extension, and therefore has minimal exposure to the Everglades marshes.

In addition to the above assumptions, discharges from STA-3/4 must continue to meet the appropriate water quality target under the “With Project” conditions. Because of the dependency of the new STA inflow volumes and phosphorus loads to the phosphorus reduction performance of the reservoirs and STA-3/4, the new STA inflow volumes and phosphorus loads will vary under the different scenarios.

In response to specific questions regarding the depth and outflow time series in the SFWMM, District staff provided the following response (J. Otero, personal communication October 10, 2006).

- The depth time series provides an appropriate range of depths in the reservoir, based on model assumptions of footprint and volume, but is not intended as a true estimate of reservoir depth. Reservoir depth time series are not recommended for calculations outside the 2x2. However, if DMSTA requires this information, the depth time series can be used as a reference for feasibility-level work.
- The releases from the reservoir are based on environmental and agricultural demand, not on a stage-discharge relationship
- Regarding seepage assumptions for the EAA reservoir, ground water is simulated based on head difference between cells in the reservoir and adjacent cells outside the reservoir. There is no explicit modeling of seepage to adjacent canals or associated reservoir seepage management features.



Final Draft - EAASR STA Preliminary Sizing Analysis

Table 2. Initial Comparison of “Without Project” and “With Project” Simulations
 Values are 35-year average annual flows in acre-feet, using May 1 – April 30 Water Year.

Destination	Source		Without Project 2050B3EAA	With Project EAA5	Difference From 2050B3EAA
Reservoir A-1	Lake Okeechobee	Reg Rel - NNRC	0	47,142	47,142
	Reservoir A-2		0	189,697	189,697
	Lake Okeechobee	Reg Rel - MC	0	345,644	345,644
	Total to A-1		0	582,482	582,482
Reservoir A-2	EAA Runoff	NNRC	0	150,744	150,744
	Reservoir A-1		0	102,366	102,366
	EAA Runoff	Miami Canal	0	122,402	122,402
	Total to A-2		0	375,511	375,511
Total to EAA SR		0	665,931	665,931	
STA-3/4 & New STA	EAA Runoff	NNRC	251,416	95,428	-155,988
	EAA Runoff	Miami Canal	225,262	95,212	-130,050
	C-139 RO	Miami Canal	13,280	13,424	144
	SSDD		3,944	4,017	73
	SFCD		11,544	11,681	136
	Lake Okeechobee	Reg Rel - NNRC	61,849	18,558	-43,291
	Lake Okeechobee	Reg Rel - MC	72,918	0	-72,918
	Lake Okeechobee	WS for STA-3/4	0	0	0
	Lake Okeechobee	WS - NNRC	41,689	8,951	-32,738
	Lake Okeechobee	WS - MC	84,241	53,769	-30,473
	Lake Okee water supply	Diverted	-58,372	-33,465	24,907
Reservoir A-1	Cell 2	0	469,179	469,179	
Total to STA-3/4 and the New STA		707,772	736,753	28,981	

Note: 1. The initial difference between simulation runs does not take into account phosphorus loads associated with the various source waters and phosphorus removal performance of the project components. Redistribution of flows from the above table will be necessary to achieve the water quality requirements of the project. The final difference between simulations will be greater than this after consideration of phosphorus performance.

Table 3. Monthly TP Concentrations Estimated for North New River Canal Runoff

Month	WY1995-2004 TP Conc	WY1995-2006 TP Conc
	ppb	ppb
Jan	39	40
Feb	59	76
Mar	61	82
Apr	83	94
May	96	100
Jun	81	87
Jul	71	76
Aug	61	67
Sep	67	80
Oct	66	77
Nov	120	118
Dec	93	99
Average	75	82



Table 4. Monthly TP Concentrations Estimated for Miami Canal Runoff

Month	WY1995-2004	WY1995-2006
	TP Conc ppb	TP Conc ppb
Jan	40	40
Feb	41	58
Mar	47	62
Apr	67	67
May	92	108
Jun	67	93
Jul	96	96
Aug	90	87
Sep	90	86
Oct	95	97
Nov	132	130
Dec	60	60
Average	82	88

Table 5A. Summary of Monthly Lake Okeechobee TP Concentrations For STA-3/4 Inflows

Month	Lake to STA via the NNRC			Lake to STA via Miami Canal		
	100	150	200	100	150	200
1	109	163	217	85	128	171
2	110	165	220	68	103	137
3	78	117	156	68	102	136
4	122	183	245	100	151	201
5	170	255	339	143	214	285
6	112	167	223	132	198	264
7	107	160	214	126	189	252
8	61	92	122	154	231	307
9	121	181	242	153	230	307
10	115	172	229	185	278	370
11	105	158	211	102	152	203
12	98	147	196	78	117	155

Table 5B. Summary of Monthly Lake Okeechobee TP Concentrations For A-1 Inflows

Month	Lake to A-1 via the NNRC			Lake to A-1 via the Miami Canal		
	100	150	200	100	150	200
1	97	145	194	74	111	149
2	98	147	196	59	89	119
3	69	104	139	59	88	118
4	109	164	218	87	131	174
5	151	227	303	124	186	248
6	99	149	199	115	172	229
7	95	143	191	110	165	219
8	55	82	109	134	200	267
9	108	161	215	133	200	267
10	102	153	204	161	241	322
11	94	141	188	88	133	177
12	87	131	174	68	101	135

DMSTA provides good flexibility in using time series of flows and depths from other hydrologic models in order to match the fundamental water balance terms. Seepage coefficients for the reservoirs were adjusted so that DMSTA outflows matched the SFWMM simulated outflow time series. Various values for the DMSTA reservoir outflow coefficients



were evaluated, however, there was considerable discrepancies with the SFWMM simulated outflows. Examination of the flow vs. depth relationship from the EAA5 scenario indicates a very complex relationship between depth and discharge, as discussed above (see **Appendix 4**). Hence, both the depth and outflow time series from SFWMM were entered as constraints for the DMSTA simulations. As expected, good agreement between the SFWMM and DMSTA results were obtained.

Each reservoir was treated separately as a single cell in DMSTA, and the TP removal is characterized by the standard DMSTA calibration data set for reservoirs (treated as 1 continuously stirred tank reactor). In addition, DMSTA allows only downstream flow among reservoirs and STAs, and therefore doesn't allow back and forth flow between the reservoirs as simulated by SFWMM. To overcome this, a pair of "dummy" reservoirs was set up upstream of the A-1 and A-2 reservoirs in order to generate an approximation of the inter-reservoir transfer of water at the appropriate TP concentration. For this analysis, the flows to STA-3/4 and the new STA were simulated to be distributed uniformly based on area, i.e., equal average hydraulic loading rate. The new STA was assumed to consist of three parallel flow-ways of equal size, and that each flow-way would consist of an emergent treatment cell (40% of the flow-way area) followed by an SAV cell (60% of the flow-way area). The analyses assume the new STA would be located along the southern boundary of the A-2 footprint – a width of 6 miles. The standard calibration data sets for the emergent vegetation and the SAV treatment performance were used.

An iterative approach was required to establish the new STA size that achieved the desired outflow TP target:

1. estimate the size using the steady-state design model;
2. calculate the inflow fraction and surface area of the new STA cells, and
3. run DMSTA.

If the long-term flow-weighted mean outflow TP did not meet the target, a new estimate of the area was calculated using the SSDM with a recalibrated K value, and steps 2 and 3 were repeated. Multiple iterations were required due to the sensitivity of the performance to the effective treatment area. Fine-tuning was required to obtain an estimate of the new effective treatment area to achieve the target to within 0.1 ppb; this fine-tuning was accomplished after multiple DMSTA runs by using the steady-state design model with adjusted K value calibrated from the associated DMSTA runs.

In addition to the sensitivity analysis of STA outflow target and lake concentrations, two additional "what-if" scenarios were evaluated. Recent evidence that the relatively low calcium concentration in Lake deliveries is not as propitious to phosphorus removal as the higher calcium concentration in EAA runoff (Dierberg et al. 2006). That study indicated a 33% reduction in the phosphorus removal performance in SAV mesocosms with Lake water compared to the performance using EAA runoff as the source water. To evaluate this effect, the effective settling rate (K) in the DMSTA simulations was reduced in proportion to the ratio of lake water to EAA runoff, resulting in a K of 43.7 m/yr for the SAV cells compared to the 52.5 m/yr from the DMSTA calibration data sets.



Similarly, the estimated size of the new STA could potentially be reduced if the phosphorus removal within the reservoirs is improved. Measures to improve this performance in the EAA reservoirs are not fully developed at this time, but evaluation of the hydraulics and vegetation characteristics of large Florida lakes suggest improved performance may result from avoiding dryout in the reservoir and relatively long hydraulic detention times (Wetland Solutions, Inc. 2004). Those goals will likely conflict with other water delivery goals for the reservoirs, and need further evaluation for their feasibility prior to firm recommendations. These hydraulic conditions could possibly support a viable SAV community, likely hydrilla, with average effective settling rates higher than the 5 m/yr used in the present analysis (Knight et al.). The present analysis used a phosphorus removal settling rate of 5 m/yr for the A-1 and A-2 reservoirs, and yielded phosphorus load reduction ranging from 15% for A-1 to 23% for A-2. This settling rate was the median of the reservoir calibration data sets (Walker and Kadlec 2005). To examine the potential effect a higher reservoir settling rate might have on the estimated size of the new STA, DMSTA was run with a settling rate of 9 m/yr for the reservoirs, equal to the 90th percentile estimate of the DMSTA calibration data sets.

6.0 PRELIMINARY ESTIMATES OF EFFECTIVE TREATMENT AREA

Using DMSTA to forecast phosphorus removal performance of the A-1 and A-2 reservoirs, as well as STA-3/4 and the proposed STA, a conceptual-level range of 0 – 17,600 acres of effective treatment area was estimated for the proposed STA. The range reflects the likely range of phosphorus removal performance of the new STA after start-up and stabilization of the treatment cells are complete. A summary of the results are presented in **Table 6**, and the related DMSTA input/output sheets are included as **Appendix 5**. Consistent with the present level of uncertainty in the PIR process, it is recommended to use a $\pm 20\%$ around the estimates in **Table 6**². Estimating the appropriate size to achieve the target outflow concentrations requires multiple iterations using DMSTA. The values presented in **Table 6** reflect multiple DMSTA analyses, and additional fine-tuning to achieve the target outflow to the 0.1 ppb. The additional fine tuning utilized the steady-state design model (SSDM) and an adjusted K calibrated against the DMSTA run. To examine the potential error introduced by this fine-tuning approximation using the SSDM, an additional DMSTA simulation was run on a scenario with a relatively large difference between the DMSTA value and the adjusted value: 150 ppb Lake with a 12 ppb target outflow concentration. The adjusted acreage using the SSDM resulted in an area approximation of 14,639 acres. Using 14,640 acres, a DMSTA simulation resulted in a long-term outflow concentration of 11.97 ppb, within a 0.1 ppb tolerance.

Figure 2 summarizes the relationship between the incremental effective treatment area as a function of the target STA outflow concentrations and the assumed concentration of Lake

² This is slightly higher than the 15-18% difference between the 10% and 90% confidence level settling rate estimates for the DMSTA calibration data sets.



Final Draft - EAASR STA Preliminary Sizing Analysis

Table 6. Preliminary Results of STA Sizing Analysis.

Lake TP			Target STA Outflow Concentration (ppb)		
Concentration ppb	Parameter	Unit	12	15	19
100	TP	ppb	11.9	15.2	19.2
	Area	acres	11,000	6,000	1,800
	TP adj	ppb	12.0	15.0	19.0
	Area adj	acres	10,835	6,248	1,938
	Total STA Outflow	AF/yr	715,044	715,044	715,044
	Total STA Load	kg/yr	10,584	13,230	16,758
	A-1 Reservoir Outflow	ppb	77	76.6	76.6
	A-1 Reservoir Load Red.	percent	15	15	15
	A-2 Reservoir Outflow	ppb	67	67.3	67.3
	A-2 Reservoir Load Red.	percent	22	22	22
	Untreated water supply diversion	AF/yr	33,465	33,465	33,465
	Water supply diversion load	kg/yr	4,128	4,128	4,128
150	TP	ppb	11.7	14.8	19.1
	Area	acres	15,300	9,900	5,130
	TP adj	ppb	12.0	15.0	19.0
	Area adj	acres	14,639	9,611	5,206
	Total STA Outflow	AF/yr	715,044	715,044	715,044
	Total STA Load	kg/yr	10,584	13,230	16,758
	A-1 Reservoir Outflow	ppb	106	106	106
	A-1 Reservoir Load Red.	percent	16	16	16
	A-2 Reservoir Outflow	ppb	71.6	71.6	71.6
	A-2 Reservoir Load Red.	percent	22	22	22
	Untreated water supply diversion	AF/yr	33,465	33,465	33,465
	Water supply diversion load	kg/yr	6,192	6,192	6,192
200	TP	ppb	11.9	15.1	19.2
	Area	acres	17,750	12,350	7,800
	TP adj	ppb	12.0	15.0	19.0
	Area adj	acres	17,593	12,456	7,958
	Total STA Outflow	AF/yr	715,044	715,044	715,044
	Total STA Load	kg/yr	10,584	13,230	16,758
	A-1 Reservoir Outflow	ppb	134	134	134
	A-1 Reservoir Load Red.	percent	16	16	16
	A-2 Reservoir Outflow	ppb	75.8	75.8	75.8
	A-2 Reservoir Load Red.	percent	23	23	23
	Untreated water supply diversion	AF/yr	33,465	33,465	33,465
	Water supply diversion load	kg/yr	8,256	8,256	8,256


Note: Long-term outflow concentrations below 15 ppb have not been demonstrated for treatment wetlands constructed on prior agricultural soils. Additional uncertainties in this analysis exist in flow estimates, reservoir operations and regional water management.



Okeechobee deliveries. **Figure 2** was developed from DMSTA results, and is not intended as a forecasting tool, merely as a graphical representation of the interplay between the most sensitive parameters influencing the size of the proposed STA.

DMSTA generates various warning and error messages based on the simulation results compared to the calibration data sets. For all simulations with a long-term average STA outflow concentration less than 15 ppb generated warning messages indicating the forecast is lower than the calibration data sets. Long-term outflow concentrations below 15 ppb have not been demonstrated for treatment wetlands constructed on prior agricultural soils. In virtually every simulation, the mean depth for SAV treatment cells was below the calibration data sets, although the absolute differences were less than 20% from the minimum. Another common warning was that the flow/width was below the range in the calibration data sets. After the final footprint of the new STA is identified, a readjustment of the flows can be examined for optimal phosphorus removal performance.

Figure 2. Summary of New Area as a Function of Target and Lake Concentrations



7.0 “WHAT-IF” ANALYSES

Lower Calcium concentrations in Lake deliveries than in EAA runoff. To evaluate the potential increase in treatment area that may be required to compensate for decreased removal performance of lower Calcium source waters, the effective settling rate (K) in the DMSTA simulations for the STAs was reduced in proportion to the ratio of lake water to EAA runoff, resulting in a K of 43.7 m/yr for the SAV cells compared to the 52.5 m/yr from the DMSTA calibration data sets. **Table 7** presents the results of this analysis, which indicated the possible additional need for 2,500-3,500 acres to meet the same outflow targets if the reduced performance observed in the mesocosm study holds true in the large-scale STAs.

Higher reservoir settling rate. To examine the potential effect a higher reservoir settling rate might have on the estimated size of the new STA, DMSTA was run with a settling rate of 9 m/yr for the reservoirs, equal to the 90th percentile estimate of the DMSTA calibration data sets. For the 12 ppb target outflow concentration and the 150 ppb Lake Okeechobee concentration scenario, the reservoirs’ removal increased to 21% and 31% for A-1 and A-2, respectively, and the TP load to STA-3/4 decreased by approximately 4.3 metric tons/yr. As a result of this decreased loading, which was equal to about 4.2% reduction in loads to the STAs, the estimated effective treatment area of the new STA decreased by approximately 770 acres, or about 5%. While additional DMSTA simulations are needed for accurate area projections, using the trends exhibited in **Tables 6 and 7** we can expect smaller (i.e., <770 acre reduction in size) decreases in area requirements for the 15 ppb and 19 ppb scenarios, and for the 100 ppb Lake scenarios; we can also expect slightly greater decreases (i.e., >770 acre reduction in size) for the 200 ppb Lake scenarios.

Table 7. Sensitivity Analysis of the Potential Effects of Calcium (Lake Okeechobee concentration of 150 ppb)

Effective Settling Rate for SAV	Parameter	Unit	Target STA Outflow Concentration (ppb)		
			12	15	19
52.5 m/yr	TP	ppb	12.0	15.0	19.0
	Area	acres	14,639	9,611	5,206
43.7 m/yr	TP	ppb	12.0	15.0	19.0
	Area	acres	18,100	12,620	7,726
	Increase in area	acres	3,460	3,009	2,520
	Increase in area	%	24%	31%	48%
	Total STA Outflow	AF/yr	710,537	713,613	716,130
	Total STA Load	kg/yr	10,542	13,197	16,780



8.0 DISCUSSION

TP performance measure: TP concentration. Florida has adopted a water quality standard for Total Phosphorus (TP) for the Everglades, with a numeric criterion of a long-term geometric mean of 10 ppb (62-302.540, F.A.C.). The water quality treatment goal for the new STA and STA-3/4 is to achieve compliance with the new TP water quality standard³. Using the set of assumptions enumerated in Sections 2 and 3 above, a range of 10,800 – 17,600 acres of additional treatment area would be required to achieve a long-term target of 12 ppb, dependant on the TP concentration of Lake Okeechobee deliveries and other factors. It is possible that these estimates may need to be increased by 2,500-3,500 acres to compensate for reduced treatment performance associated with the Calcium concentrations in Lake water. While long-term outflow concentrations below 15 ppb have not been demonstrated for treatment wetlands constructed on prior agricultural soils, an annual flow-weighted mean outflow concentration of 11 ppb was observed during WY2004 for STA-6⁴, and 13 ppb was observed for STA-3/4 during WY2005 (Pietro et al. 2006). The target concentrations used in this analysis are long-term flow-weighted means over the 35 water years of the simulation period. Simulated outflow concentrations varied considerably on an annual basis, as depicted in **Figure 3**, which depicts the results of the simulations for 150 ppb concentration for Lake Okeechobee deliveries. For the 12 ppb scenario, annual outflow concentrations varied from a minimum of 5.6 ppb to a maximum of 18.9 ppb, a range of -53% to +56% around the long-term flow-weighted mean. A range of 6,200 - 12,500 acres of additional treatment area was estimated for a long-term target of 15 ppb, dependant on the TP concentration of Lake Okeechobee deliveries and other factors. A range of 1,900 – 8,000 acres of additional treatment area was estimated for a long-term target of 19 ppb, dependant on the TP concentration of Lake Okeechobee deliveries and other factors.


TP performance measure – TP load. Performance Measure GE-5 (TP Loads) cites the methods and results of the 2003 Long-Term Plan, which forecast TP loads from STA-3/4 for the period 2050 of 10.2-15.3 metric tons/year, corresponding to long-term flow-weighted mean concentrations of 14-21 ppb and an annual average flow of 590,694 AF/yr. By comparison, this analysis estimated TP loads from the STAs ranging from 10.6 metric tons/yr to 16.8 metric tons per year, corresponding to long-term flow-weighted mean concentrations of 12-19 ppb. The present analyses are based on annual average outflows from the STAs of approximately 715,000 AF/yr, representing a 21% increase in the volume of water treated compared to the 2003 Long-Term Plan estimates.

³ The Florida Department of Environmental Protection is responsible for establishing effluent limitations for discharges into the Everglades Protection Area to ensure compliance with water quality standards. FDEP has not yet established a Water-Quality Based Effluent Limitation (62.650 F.A.C.) for discharges into the Everglades. The use of target outflow concentrations in this analysis does not in any way pre-ordain what the ultimate discharge limit will be.

⁴ Approximately 28% (245 acres) of STA-6 is prior-existing wetlands, and not former agricultural lands.



Figure 3.



Diversion of untreated water supply. For this analysis, untreated water supply diversions to multiple downstream waters were taken directly from the SFWMM output for the EAA5 scenario, and averaged 32,755 AF/yr. The majority of this (20,553 AF/yr) was directed to the Seminole Big Cypress reservation. The balance was sent to the Lower East Coast to meet water supply demands. It may be possible to make low flow water supply deliveries at times when water levels in the Water Conservation Areas (WCAs) are below certain minimum elevations such that the water remains within the canals and does not overflow into the adjacent marsh.

Determination of Incremental Treatment Area Requirements Associated with the EAA Storage Reservoirs. Section 2 described a Sizing Strategy for the proposed STA associated with the EAASR. A preliminary estimate of the flows and phosphorus levels associated with the “With Project” and “Without Project” conditions is presented in **Table 8**. Unfortunately, insufficient certainty exists at this time to finalize the recommendation for the size of the proposed STA. Assuming the final “With Project” flow volumes and sources do not change significantly, the most sensitive parameters influencing the size of the STA remain the target outflow TP concentration and the Lake Okeechobee delivery TP concentration. Another critical sizing parameter is the possible reduction in STA performance compared to the DMSTA forecast projections resulting from lower Calcium concentrations than were present in the SAV calibration data sets. Once the critical STA sizing parameters (STA target TP, Lake delivery TP and Calcium effect on STA performance) are established, and final regional SFWMM scenarios for the “With Project” and “Without Project” scenarios are



Final Draft - EAASR STA Preliminary Sizing Analysis

completed, an additional analysis will be required to determine the incremental treatment area requirement associated with the EAASR.

Table 8. Comparison of Annual Flows and Phosphorus Levels

Lake Deliveries	Plan	Parameter	Unit	Average Annual Inflow To STA-3/4 and the New STA					Difference
				From Lake		Basin Runoff		Total	
				Direct	Indirect (Through A-1)	Direct	Indirect (Through A-1)		
100 ppb	Without Project EAA2050B3	Flow	AF/yr	202,325	0	505,447	0	707,772	
		TP Load	kg/yr	24,957	0	54,781	0	79,738	
		TP Conc	ppb	100		88		91	
	With Project EAA5	Flow	AF/yr	47,813	316,382	219,761	152,797	736,753	28,981
		TP Load	kg/yr	5,898	28,761	25,141	13,890	73,690	-6,048
		TP Conc	ppb	100	74	93	74	81	-10
150 ppb	Without Project EAA2050B3	Flow	AF/yr	202,325	0	505,447	0	707,772	
		TP Load	kg/yr	37,435	0	54,781	0	92,216	
		TP Conc	ppb	150		88		106	
	With Project EAA5	Flow	AF/yr	47,813	316,382	219,761	152,797	736,753	28,981
		TP Load	kg/yr	8,847	40,099	25,141	19,366	93,453	1,237
		TP Conc	ppb	150	103	93	103	103	-3
200 ppb	Without Project EAA2050B3	Flow	AF/yr	202,325	0	505,447	0	707,772	
		TP Load	kg/yr	49,914	0	54,781	0	104,694	
		TP Conc	ppb	200		88		120	
	With Project EAA5	Flow	AF/yr	47,813	316,382	219,761	152,797	736,753	28,981
		TP Load	kg/yr	11,795	51,320	25,141	24,785	113,042	8,348
		TP Conc	ppb	200	132	93	132	124	4

The following is a *hypothetical scenario* that illustrates the method described in Section 2 to determine an initial estimate of the incremental treatment area requirements associated with the EAASR. For the purpose of this *hypothetical scenario*, an STA outflow target is established at 15 ppb; FDEP will establish the final effluent limitation in accordance with 62-650, F.A.C.

STA Sizing Strategy (from Section 2)

1. The 2050B3EAA and the EAA5 simulations describe the volumes and sources of water to the reservoirs and STAs for the “Without Project” and “With Project” conditions, respectively.
2. The best professional judgment of Lake Okeechobee managers suggests that the long-term TP concentration in Lake deliveries is forecast to be 150 ppb. The phosphorus concentrations in basin runoff are equal to the values used in this analysis.



3. The effect of Calcium in Lake deliveries is forecast to reduce STA performance in proportion to the ratio of lake water to EAA runoff. Phosphorus removal within the reservoirs can be forecast using the default characteristics of DMSTA.
4. The flows and phosphorus levels for the “With Project” and “Without Project” conditions are described in **Table 8**.
5. For the “Without Project” condition, DMSTA simulations indicate that an additional 6,000 acres is needed to achieve the target outflow concentration. For the “With Project” condition, DMSTA simulations indicate that 12,620 acres is needed to achieve the target outflow concentration (as shown in **Table 7**). The difference between the 12,620 acres for the “With Project” condition and the 6,000 acres for the “Without Project” condition, or 6,620 acres, would be an initial estimate of the incremental treatment area requirement associated with the EAASR.

Uncertainty in Flows. Although the uncertainty in the flow time series in SFWMM used as input to DMSTA is not readily nor easily quantifiable, flow estimates will be revised in the near term. The model simulations and iterations between SFWMM and DMSTA, being considered by the project team, along with SFWMM simulations to meet programmatic requirements, will produce multiple revisions of flow estimates, as described in **Table 9** below.

Next Steps. Once the critical STA sizing parameters (STA target TP, Lake delivery TP and Calcium effect on STA performance) are established, the results and methodology presented in this preliminary sizing analysis and related sensitivity analysis should allow the PDT to move forward in completing the PIR. Suggested issues to address include:

1. **Changing conditions.** An appropriate adaptive management approach could be developed for addressing the inevitable future changes in the following areas.
 - a. “With Project” flows; an iterative process of hydrologic and water quality modeling will likely be required to finalize the “With Project” conditions (e.g., to exclude runoff from the new STA footprint) and to determine the ultimate inflow volume and associated phosphorus load to be treated in the new STA.
 - b. Revisions to the STA effluent limitations, including establishment of the Water-Quality Based Effluent Limitations which will replace the target STA TP concentrations used in this study.
 - c. Revised forecasts of the Lake Okeechobee discharge phosphorus levels as CERP and other projects combine to aid in the recovery of the Lake.
 - d. Revised forecasts of STA performance, as large-scale enhancements and expansions are implemented, and the effects of, and management options for, Calcium are better understood.
 - e. Revised forecasts of the EAA runoff phosphorus concentrations, particularly if the recent increasing trend continues.



Table 9. Description of SFWMM Simulations Associated with the EAASR.

Model Simulation or Iteration	Name of Flows	Description of Modeling
1	EAA5	The EAA5 run produced initial estimates of flows that are being used by the DMSTA in the preliminary sizing of the new STA for the EAA Storage Reservoir.
2	2050B4	The new 2050B4-like base will include Alt1, CSOP, and LORSS TSP. Operational modifications will be made to meet the long-term inflow targets for not exceeding treatment capacity of STA 2, Compartment B, and STA 3 / 4. The resulting flows would be checked with DMSTA.
3	2050B4_x	If the 2050B4-like flows do not meet the treatment requirements of the STAs, iterations of the 2050B4-like run may be needed.
4	NAI	The reservoir and the preliminary size of the new STA will be incorporated into the 2050B4-like base. Operational modifications will be made to meet the long-term inflow targets for the STAs, as well as all other assumptions, constraints, and operational intent as part of the NAI. Flows from this new NAI would be checked with DMSTA for not exceeding treatment capacity of STA 2, Compartment B, and STA 3 / 4; and to finalize the size of the new STA.
5	NAI_x	If the NAI flows do not meet the treatment requirements of the STAs, iterations of the NAI run may be needed.
6	2010Base	The appropriate assumptions of the 2050B4-like base will be incorporated into a 2010 base. Operational modifications may be necessary. These flows would be checked for not exceeding treatment capacity of the STAs.
7	2010Base_x	If the 2010 base flows exceed the treatment capacity of the STAs, iterations of the 2010 base run may be needed.
8	IOR	The reservoir and new STA will be incorporated in the 2010 base to produce the 2010 with project or IOR run, and operational modifications would be made to meet targets, assumptions, constraints, and operational criteria similarly to what was done with the NAI run. This simulation will be used for project assurances and savings clause analysis. Flows would be checked with DMSTA.
9	IOR_x	If the IOR flows exceed the treatment capacity of the STAs, iterations of the IOR run may be needed.
10	Ops	For project operations, it will be necessary to describe operational rules for the reservoir. This information is not readily available from the IOR run, since the environmental deliveries are based on daily triggers at various locations within the Everglades and are not easily translated into rules that operators can use. A simulation of the reservoir operations may require an operational model, which may result in different flows than the IOR. If the operational model does not include STA treatment, these flows would be checked with DMSTA.
11	Ops_x	If the operational flows exceed the treatment capacity of the STAs, iterations of the operational model may be needed.



Final Draft - EAASR STA Preliminary Sizing Analysis

2. **STA Design.** The design of the new STA should build on the lessons learned from the design, construction and operation of the Everglades STAs, and incorporate the most effective phosphorus removal features available.
3. **Refinement of Reservoir Operations and Possible Configuration Revision.** There may be considerable opportunity to refine the operations of the EAASR treatment cells in order to enhance the performance of the STAs. For example, it is noted that the annual volume of water projected to enter the combined 30,000-acre EAASR was less than the annual inflow volume to STA-3/4 – even though the STA is approximately 50% of the area. This may also suggest that a portion of the footprint designated for the EAASR might be more effectively utilized for the proposed STA, although more rigorous hydraulic modeling will be necessary to ensure the hydraulic constraints and storage requirements of the EAASR are preserved. In addition, the estimated size of the new STA could potentially be reduced if the phosphorus removal within the reservoirs is improved from the 15-22% range forecast in this analysis. Measures to improve this performance are not fully developed at this time, but evaluation of the hydraulics and vegetation characteristics of large Florida lakes suggest improved performance may result from avoiding dryout in the reservoir and relatively long hydraulic detention times. Those goals will likely conflict with other water delivery goals for the reservoirs, and need further evaluation for their feasibility prior to firm recommendations.
4. **Integration with Compartment B.** Consistent with the conditions simulated by EAA5, no consideration was given to integrating the operation of the EAASR and the STAs with the treatment area being designed for Compartment B. Developing an integrated regional operations strategy, as planned in the future SFWMM simulations described in Table 9, will likely minimize the additional treatment area of the proposed STA and enhance the overall STA performance, thereby ensuring the highest quality of water entering the Everglades.

8.0 REFERENCES

- ADA Engineering, Inc. and Burns and McDonnell Engineering Inc. 2005. Everglades Agricultural Area Regional Feasibility Study, prepared for the South Florida Water Management District. October 2005.
- Black and Veatch 2006. EAA Storage Reservoir A1 Basis of Design Report. Prepared for the South Florida Water Management District. January 2006.
- Dierberg, F., DeBusk, T., Owens, P. and S. Jackson. 2006. The Influence of Calcium on Phosphorus Removal and Retention in Submerged Aquatic Vegetation Communities in South Florida Wetlands. DB Environmental, Inc. 2006 GEER Conference.
- Goforth, G. 2006. Conceptual-level Sizing Analysis of the Proposed EAASR STA. Prepared for the South Florida Water Management District. August 12, 2006.



Final Draft - EAASR STA Preliminary Sizing Analysis

Knight, R., B Gu, R. Clarke, and J. Newman. Long-Term Phosphorus Removal in Florida Aquatic Systems Dominated by Submerged Aquatic Vegetation.

Pietro, K. R Bearzotti, M. Chimney, G. Germain, N. Iricanin and T. Piccone 2006. Stormwater Treatment Area (STA) Performance, Compliance and Optimization. In Volume 1 Chapter 5 of the Draft 2007 South Florida Environmental Report.

Walker, W. 1995. Design Basis for Everglades Stormwater Treatment Areas. In Water Resources Bulletin, American Water Resources Association, Vol. 31, no. 4. August 1995.

Walker, W. and R. Kadlec 2005. Dynamic Model for Stormwater Treatment Areas Version 2, prepared for the U.S. Dept. of Interior and U.S. Army Corps of Engineers, May 2005.

Wetland Solutions, Inc. 2004. Water Quality Assessment Report Everglades Agricultural Area Storage Reservoirs – Phase 1 A. Alternative Plan Formulation And Evaluation. Prepared for U.S. Army Corps of Engineers. September 2004.

CERTIFICATION

I hereby certify, as a Professional Engineer in the State of Florida, that the information in this report was assembled under my direct personal charge. This report is not intended or represented to be suitable for reuse without specific verification or adaptation by the Engineer. This certification is made in accordance with the provisions of the Laws and Rules of the Florida Board of Professional Engineers under Chapter 61G15-29, Florida Administrative Code.

Gary F. Goforth, P.E. Florida P.E. # 35525

Date: _____

Reproductions are not valid unless signed, dated and embossed with Engineer's seal



APPENDIX 1. CRITICAL ASSUMPTIONS INCORPORATED INTO THIS ANALYSIS

	Critical Issue	Background	Assumption For This Sizing Analysis	Outstanding Questions
1	What is the target STA outflow TP target, estimated as a long-term average annual value?	<p>1. Florida has adopted a water quality standard for Total Phosphorus (TP) for the Everglades, with a numeric criterion of a long-term geometric mean of 10 ppb (62-302.540, F.A.C.). The water quality treatment goal for the new STA and STA-3/4 is to achieve compliance with the new TP water quality standard. FDEP has not yet established a Water-Quality Based Effluent Limitation (62.650 F.A.C.) for discharges into the Everglades.</p> <p>2. Performance Measure GE-4 (TP Concentrations) cites the TP water quality standard for the Everglades; it was noted that the performance measure inaccurately describes the TP water quality standard and criterion.</p> <p>3. Performance Measure GE-5 (TP Loads) cites the methods and results of the 2003 Long-Term Plan, which forecast 2050 TP loads from STA-3/4 of 10.2-15.3 metric tons/year corresponding to long-term flow-weighted mean concentrations of 14-21 ppb.</p>	<p>FDEP will establish the effluent limitations in accordance with the State process, however, the results will not be available in time for this analysis.</p> <p>For the purpose of this analysis, a range of long-term outflow flow-weighted mean TP concentration targets will be used. A lower value of 12 ppb was suggested by Bob Kadlec, derived from multiplying 10 ppb by his estimate of the ratio of flow-weighted mean:geometric mean outflow concentrations observed at the STAs. A second target of 15 ppb was identified as the lowest flow-weighted mean concentration observed in the calibration data set for a large-scale treatment cell constructed on prior agricultural land. A third target of 19 ppb will be used as an upper bound on the sensitivity analysis.</p> <p>Reporting of DMSTA results will include an appropriate footnote indicating that long-term average values below 15 ppb are lower than have been observed. The distribution of annual outflow concentrations will be reported, but there will be no additional simulations conducted to achieve any specific annual maximum value.</p> <p>The annual loads forecast by the sensitivity analysis above will be compared to the 2003 LTP forecast loads (10.2 - 15.3 metric tons/yr) to determine if an additional scenario is needed to achieve these targets.</p>	



Final Draft - EAASR STA Preliminary Sizing Analysis

	Critical Issue	Background	Assumption For This Sizing Analysis	Outstanding Questions
2	What is the appropriate TP concentration to use for Lake Okeechobee deliveries to the EAA reservoirs and the STAs?	Various planning documents assumed TP concentrations in Lake deliveries at levels quite a bit lower than has been observed since the 2004 hurricanes.	For the purpose of this analysis, a sensitivity analysis will be performed using TP concentrations with a Base Condition of 150 ppb, a low end of 100 ppb and a high end of 200 ppb. Monthly variations in Lake concentrations will be applied.	
3	What is the appropriate TP concentration to use for EAA runoff to the reservoirs and STAs?	Various planning documents assumed TP concentrations in EAA runoff at levels lower than has been observed since the 2004 hurricanes. The District is conducting an analysis of this phenomenon, but results are not expected to be available in time for this STA sizing analysis. A preliminary analysis of WY2005 and WY2006 inflows to STA-3/4 indicate that the TP concentration from the S-7/S-2 basin (North New River Canal) has increased from a 10-yr average of 75 ppb (WY1995-2004) to a 12-yr average of 82 ppb. A similar analysis indicates that the TP concentration from the S-8/S-3 basin (Miami Canal) has increased from a 10-yr average of 82 ppb to a 12-yr average of 88 ppb.	The 12-year average monthly TP concentrations for EAA runoff will be used in lieu of the 10-year monthly concentrations used in the EAA Regional Feasibility Study.	



Final Draft - EAASR STA Preliminary Sizing Analysis

	Critical Issue	Background	Assumption For This Sizing Analysis	Outstanding Questions
4	What phosphorus removal characteristic is appropriate for STA-3/4 and the new STA?	Evidence at various scales suggest that phosphorus removal in a treatment wetland may be less in systems with lower Calcium inflows than in the DMSTA calibration data sets. A reduction of 33% in the effective settling rate was observed by Dierberg et al. (2006) for a recent mesocosm study.	The DMSTA parameters for the EMG_3 and SAV_3 will be used as the Base Condition. An additional set of simulations will be conducted using a reduced K value for SAV treatment cells based on the volumetric ratio of Lake water and EAA runoff; the settling rate will be reduced by 16.8%.	
5	What phosphorus removal characteristic is appropriate for the reservoirs?	Evidence from large Florida lakes indicate that phosphorus removal in the reservoirs may be better than predicted using the standard DMSTA RES_3 parameter values if the operations are modified to minimize dryout and maintain shallower depths.	The standard RES_3 parameter values will be used for the Base Condition. An additional simulation will be conducted using an increased K value of 9 m/yr, equal to the 90 th percentile of the DMSTA calibration data sets for reservoirs.	
6	Should water supply deliveries that are simulated in the 2x2 model as going around the reservoirs and STAs be routed through the STAs for treatment?	The EAA1_4 scenario of the 2x2 model simulated approximately 68,000 AF/yr of water supply deliveries around the reservoirs and STAs to downstream users, including the Seminole Indian reservation and the Lower East Coast.	Use the flows generated by the 2x2 model	




Final Draft - EAASR STA Preliminary Sizing Analysis

	Critical Issue	Background	Assumption For This Sizing Analysis	Outstanding Questions
7	Can long-term high performance of large SAV treatment cells be sustained in spite of hurricanes and drought?	The large SAV cells in STA-1W and STA-2 suffered extensive vegetative disruption during the 2004 and 2005 hurricanes. The District is currently incorporating parallel bands of emergent vegetation in SAV cells to shorten the wind fetch and minimize future disruption. As part of the on-going STA enhancements, the large SAV cells are being retrofit with water supply pumps to minimize dryout.	Use the standard DMSTA SAV_3 parameter values for this analysis.	Beyond the scope of this analysis, but a critical question none-the-less: Will the vegetation strips increase the resiliency of SAV cells?



APPENDIX 2. SFWMM Flow Terms and Distributions.



**APPENDIX 3. DEVELOPMENT OF WY1995-2006 MONTHLY
CONCENTRATIONS FOR NORTH NEW RIVER AND MIAMI CANAL RUNOFF**

In recognition of the increased TP concentrations in EAA runoff over the past two water years, the 1995-2004 period of record used by ADA/B&M in the EAA RFS was adjusted to include WY2005 and 2006. The resulting 12-year period of record monthly TP concentrations were used to develop daily time series of TP inflows to the reservoirs and STAs. In order to estimate the influence of WY2005 and WY2006 on the 10-year period of record developed by ADA/B&M (2005) in the brief time available for this analysis, it was necessary to assume that sources other than the EAA and Lake Okeechobee did not significantly influence the STA-3/4 inflow concentrations during WY2004 and WY2005. The degree to which other sources influenced the inflow concentrations would influence these results. Lake inflows to STA-3/4 for WY2005 and WY2006 were provided by District staff. Negative loads were set to zero. For WY2006, it was assumed that Lake deliveries entered STA-3/4 via G-370; any excess, i.e., greater than the total inflow to G-370, was assumed to enter G-372.

Results for the Miami Canal

10-Year Period of Record Results from the EAA Regional Feasibility Study (ADA/Burns & McDonnell)

Month	WY1995-2004		
	Flow AF	TP Load kg	TP Conc ppb
Jan	13,162	652	40
Feb	18,772	959	41
Mar	12,152	698	47
Apr	10,107	840	67
May	17,114	1,944	92
Jun	45,719	3,758	67
Jul	36,230	4,303	96
Aug	40,839	4,555	90
Sep	45,152	5,001	90
Oct	38,284	4,479	95
Nov	26,486	4,317	132
Dec	27,213	2,013	60
Average	331,230	33,519	82



Final Draft - EAASR STA Preliminary Sizing Analysis

WY2005 Total			WY2005 LO			WY2005 runoff		
Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb
7,063	671	77	1,613	404	203	5,451	267	40
14,993	3,484	188	9,136	2,983	265	5,857	501	69
58,556	5,844	81	1,356	393	235	57,200	5,451	77
24,352	6,258	208	23,984	6,779	229	0	0	
23,088	4,756	167	1,106	71	52	21,982	4,685	173
137,389	22,927	135	3,751	260	56	133,638	22,667	138
83,563	9,880	96	3,120	188	49	80,443	9,692	98
27,908	2,274	66	-59	0	0	27,967	2,274	66
27,055	1,839	55	-3,196	0	0	30,251	1,839	49
66,363	8,268	101	290	-19	-53	66,072	8,287	102
24,938	3,674	119	0	0		24,938	3,674	119
1,167	79	55	1,017	94	75	0	0	
496,434	69,953	114	42,118	11,153	215	453,798	59,336	106

WY2006 total			WY2006 LO			WY2006 runoff		
Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb
17,023	3,974	189	17,008	3,973	189	15	0	24
24,249	5,621	188	0	0		24,249	5,621	188
8,247	1,799	177	0	0		8,247	1,799	177
3,452	604	142	4,588	763	135	0	0	
23,088	4,756	167	0	0		23,088	4,756	167
137,389	22,927	135	0	0		137,389	22,927	135
83,563	9,880	96	0	0		83,563	9,880	96
27,908	2,274	66	0	0		27,908	2,274	66
27,055	1,839	55	0	0		27,055	1,839	55
66,363	8,268	101	0	0		66,363	8,268	101
24,938	3,674	119	0	0		24,938	3,674	119
1,167	79	55	0	0		1,167	79	55
444,441	65,695	120	21,596	4,736	178	423,981	61,117	117

WY1995-2006		
Flow AF	TP Load kg	TP Conc ppb
11,424	566	40
18,152	1,309	58
15,581	1,186	62
8,423	700	67
18,017	2,407	108
60,685	6,931	93
43,859	5,217	96
38,689	4,175	87
42,402	4,474	86
42,940	5,112	97
26,228	4,210	130
22,775	1,684	60
349,173	37,970	88



Final Draft - EAASR STA Preliminary Sizing Analysis

Results for the North New River Canal

10-Year Period of Record Results from the EAA Regional Feasibility Study (ADA/Burns & McDonnell)

Month	WY1995-2004		
	Flow AF	TP Load kg	TP Conc ppb
Jan	5,020	242	39
Feb	11,094	809	59
Mar	9,926	748	61
Apr	6,634	679	83
May	10,120	1,195	96
Jun	29,428	2,923	81
Jul	27,775	2,447	71
Aug	23,675	1,777	61
Sep	26,349	2,170	67
Oct	25,075	2,032	66
Nov	15,611	2,307	120
Dec	14,069	1,614	93
Average	204,776	18,943	75

WY2005 total inflows			WY2005 LO			WY2005 runoff		
Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb
4,171	509	99	1,111	292	213	3,061	217	58
13,277	2,877	176	9,023	2,730	245	4,254	147	28
30,822	3,898	103	960	349	295	29,862	3,549	96
24,441	6,494	215	23,359	5,476	190	1,082	1,018	763
270	18	54	270	55	165	0	0	
15,971	2,086	106	28	7	204	15,944	2,079	106
17,980	2,558	115	107	17	129	17,873	2,541	115
92,617	9,527	83	0			92,617	9,527	83
66,584	10,996	134	0			66,584	10,996	134
12,054	1,897	128	0			12,054	1,897	128
0	0		0			0	0	
27,052	5,839	175	17,659	3,667	168	9,393	2,172	187
305,238	46,699	124	52,516	12,593	194	252,721	34,143	110



Final Draft - EAASR STA Preliminary Sizing Analysis




WY2006 total inflows			WY2006 Lake			WY2006 Runoff		
Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb	Flow AF	TP Load kg	TP Conc ppb
17,793	4,249	194	34,801	8,222	192	0	0	
18,039	4,316	194	356	44	100	17,683	4,272	196
9,119	3,037	270	238	31	106	8,881	3,006	274
0	0		4,588	763	135	0	0	
23,138	5,056	177	16,117	3,606	181	7,021	1,450	167
71,862	9,558	108	3	1	246	71,859	9,557	108
24,854	2,960	97	188	16	69	24,666	2,944	97
13,035	853	53	100	8	65	12,936	845	53
22,668	1,900	68	189	12	52	22,479	1,888	68
42,705	6,835	130	0	0		42,705	6,835	130
8,499	813	78	153	13	69	8,346	800	78
1,008	104	84	66	4	49	942	100	86
252,721	39,680	127	56,799	12,720	182	217,518	31,696	118

WY1995-2006		
Flow AF	TP Load kg	TP Conc ppb
4,438	220	40
11,073	1,042	76
11,500	1,170	82
5,618	651	94
9,018	1,117	100
31,840	3,406	87
26,691	2,496	76
28,525	2,345	67
29,379	2,882	80
25,459	2,421	77
13,705	1,989	118
12,585	1,534	99
209,833	21,272	82






APPENDIX 4. RESERVOIR OUTFLOW-DEPTH RELATIONSHIPS

A-1 Outflows



A-2 Outflows



APPENDIX 5. DMSTA SUMMARY SHEETS

Index to DMSTA Input/Output Sheets

Page 33 100 pp Lake Okeechobee Scenario – A-1 Reservoir Input/Output
Page 34 100 pp Lake Okeechobee Scenario – A-2 Reservoir Input/Output
Page 35 100 pp Lake Okeechobee Scenario – STA Input/Output 12 ppb
Page 36 100 pp Lake Okeechobee Scenario – STA Input/Output 15 ppb
Page 37 100 pp Lake Okeechobee Scenario – STA Input/Output 19 ppb
Page 38 150 pp Lake Okeechobee Scenario – A-1 Reservoir Input/Output
Page 39 150 pp Lake Okeechobee Scenario – A-2 Reservoir Input/Output
Page 40 150 pp Lake Okeechobee Scenario – STA Input/Output 12 ppb
Page 41 150 pp Lake Okeechobee Scenario – STA Input/Output 15 ppb
Page 42 150 pp Lake Okeechobee Scenario – STA Input/Output 19 ppb
Page 43 200 pp Lake Okeechobee Scenario – A-1 Reservoir Input/Output
Page 44 200 pp Lake Okeechobee Scenario – A-2 Reservoir Input/Output
Page 45 200 pp Lake Okeechobee Scenario – STA Input/Output 12 ppb
Page 46 200 pp Lake Okeechobee Scenario – STA Input/Output 15 ppb
Page 47 200 pp Lake Okeechobee Scenario – STA Input/Output 19 ppb
Page 48 150 pp Lake Okeechobee Scenario – STA Input/Output 12 ppb w/ Adj. K for SAV
Page 49 150 pp Lake Okeechobee Scenario – STA Input/Output 15 ppb w/ Adj. K for SAV
Page 50 150 pp Lake Okeechobee Scenario – STA Input/Output 19 ppb w/ Adj. K for SAV
Page 51 150 pp Lake Okeechobee Scenario – A-1 Reservoir Input/Output w/ Adj. K for RES
Page 52 150 pp Lake Okeechobee Scenario – A-2 Reservoir Input/Output w/ Adj. K for RES
Page 53 150 pp Lake Okeechobee Scenario – STA Input/Output 12 ppb w/ Adj. K for RES



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	A1	Compartment A-1												
Input Series Name	-	TS_A1	15,200 acres (from A8)												
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation												
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation												
Starting Date for Output	-	05/01/65													
Integration Steps Per Day	-	4													
Number of Iterations	-	0	Simulation Type:												
Output Averaging Interval	days	30	Output Variable	Mean	Lower CL	Upper CL	Diagnostics								
Inflow Conc Scale Factor	-	1	FWM Outflow C (ppb)	76.6	#N/A	#N/A	H2O Balance Error Mean & Max	0.0%	0.0%						
Rainfall P Conc	ppb	10	GM Outflow C (ppb)	72.5	#N/A	#N/A	Mass Balance Error Mean & Max	0.0%	0.0%						
Atmospheric P Load (Dry)	mg/m2-yr	20	Load Reduction %	15%	#N/A	#N/A	Iterations & Convergence	2	0.7%						
			Bypass Load (%)	0.0%			Warning/Error Messages	1							
Cell Number -->		1	2	3	4	5	6	7	8	9	10	11	12		
Cell Label	-->	RES_3													
Vegetation Type	-	1													
Inflow Fraction	-	1													
Downstream Cell Number	-	1													
Surface Area	km2	61.54													
Mean Width of Flow Pt	km	6.70													
Number of Tanks in Series	-	1.0													
Minimum Depth for Releases	cm	15													
Release 1 Series Name	-	IRRIG													
Release 2 Series Name	-	TO_A2													
Outflow Series Name	-	TO_STA													
Depth Series Name	-	A1 DEPTH													
Outflow Control Depth	cm														
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	1.5													
Outflow Coefficient - Intercept	-	8													
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day	9.05233													
Inflow Seepage Rate	(cm/d) / cm														
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.00081													
Outflow Seepage Control Elev	cm	6													
Max Outflow Seepage Conc	ppb	100													
Seepage Recycle to Cell Number	-	1													
Seepage Recycle Fraction	-	0.75													
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	105													
Initial P Storage Per Unit Area	mg/m2	525													
Initial Water Column Depth	cm	150													
C0 = Conc at 0 g/m2 P Storage	ppb	3													
C1 = Conc at 1 g/m2 P storage	ppb	150													
C2 = Conc at Half-Max Uptake	ppb														
K = Net Settling Rate at Steady State	m/yr	5.0													
Z1 = Saturated Uptake Depth	cm	40													
Z2 = Lower Penalty Depth	cm	100													
Z3 = Upper Penalty Depth	cm	400													
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.56													1.56
Run Date	-	10/10/06													10/10/06
Starting Date for Simulation	-	01/01/65													01/01/65
Starting Date for Output	-	05/01/65													05/01/65
Ending Date	-	04/30/00													04/30/00
Output Duration	days	12784													12784
Cell Label	-	1													Total
Downstream Cell Label	-	1													-
Network Simulation Name	-	EAASR_NET													EAASR_NET
Simulation Type	-	Base													Base
Surface Area	km2	61.54													61.54
Mean Rainfall	cm/yr	130.73													130.7
Mean ET	cm/yr	135.34													135.3
Cell Inflow Volume	hm3/yr	717.8													717.8
Cell Inflow Load	kg/yr	64136.0													64136
Cell Inflow Conc	ppb	89													89.4
Treated Outflow Volume	hm3/yr	578.3													578.3
Treated Outflow Load	kg/yr	44318.3													44316
Treated FWM Outflow Conc	ppb	77													76.6
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Total Outflow Volume - Bypass	hm3/yr	701.7													701.7
Total Outflow Load - Bypass	kg/yr	54416.8													54416.8
Total FWM Outflow Conc	ppb	77.5													77.5
Bypass Load	kg/yr	0													0.0
Bypass Load	%	0%													0.0
Maximum Inflow	hm3/d	11.90													11.90
Maximum Outflow	hm3/d	9.01													9.01
Surface Load Reduction	kg/yr	19820													19820
Load Trapped in Sediments	kg/yr	10598													10598
Overall Load Reduction	%	15%													15%
Lower Confidence Limit	%	#N/A													#N/A
Upper Confidence Limit	%	#N/A													#N/A
Daily Geometric Mean	ppb	67.7													#N/A
Outflow Geo Mean - Composites	ppb	72.5													72.5
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Frequency Outflow Conc > 10 ppb	%	100%													100%
Frequency Outflow Conc > 20 ppb	%	100%													100%
Frequency Outflow Conc > 50 ppb	%	81%													100%
Freq Outflow Volume > 10 ppb	%	82%													82%
95th Percentile Outflow Conc	ppb	199.53													200
Mean Biomass P Storage	mg/m2	412													412
Storage Increase / Net Removal	%	1%													1%
Net Storage Turnover Rate	1/yr	14.6													14.6
Unit Area P Load	mg/m2-yr	1042													1042
Unit Area P Removal	mg/m2-yr	172													172
Mean Water Load	cm/d	3.2													3.2
Max Water Load	cm/d	19.3													19.3
Mean Depth	cm	220													220
Minimum Depth	cm	1.0													1
Maximum Depth	cm	379.5													379
Frequency Depth < 10 cm	%	6%													5.6%
Flow/Width	m2/day	293													293.3
HRT Days	days	68.8													68.8
Mean Velocity	cm/sec	0.15													0.15
Seepage Outflow / Total Outflow	%	1%													2%
Release 1 Outflow Volume	hm3/yr	0.00													0.0
Release 2 Outflow Volume	hm3/yr	123.43													123.4
95th Percentile Outflow Volume	hm3/d	4.8													4.8
95th Percentile Outflow Load	kg/d	399.1													399.1
Simulated / Specified Mean Depth	%	99%													1.0
Release 1 Demand Met	%	#N/A													#N/A
Release 2 Demand Met	%	98%													1.0
Outflow Demand Met	%	100%													1.0
Range Check - Mean Depth	-														0
Range Check - Freq Depth < 10 cm	-	10.00													1
Range Check - Flow/Width	-														0
Range Check - Inflow Conc	-														0
Range Check - Outflow Conc	-														0
Water Balance Error	%	0.00%													0.00%
Mass Balance Error	%	0.00%													0.00%
Warning or Error Messages		Cell 1 Freq 2 < 10 cm out of calib. range for RES_3. 0 vs. 0 - 0%													1



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:													
Design Case Name	-	A2	Compartment A-2													
Input Series Name	-	T5_A2	13,775 acres of effective area													
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation													
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation													
Starting Date for Output	-	05/01/65														
Integration Steps Per Day	-	4														
Number of Iterations	-	0														
Output Averaging Interval	days	30														
Inflow Conc Scale Factor	-	1														
Rainfall P Conc	ppb	10														
Atmospheric P Load (Dry)	mg/m2-yr	20														
Simulation Type:			Mean	Lower CL	Upper CL	Diagnostics										
Output Variable			FWM Outflow C (ppb)	67.3	#N/A	#N/A	H2O Balance Error Mean & Max	0.0%	0.0%							
			GM Outflow C (ppb)	70.8	#N/A	#N/A	Mass Balance Error Mean & Max	0.0%	0.0%							
			Load Reduction %	22%	#N/A	#N/A	Iterations & Convergence	3	0.0%							
			Bypass Load (%)	0.0%			Warning/Error Messages	1								
Cell Number -->	-	1	2	3	4	5	6	7	8	9	10	11	12			
Cell Label	-->	RES_A2														
Vegetation Type	-->	RES_3														
Inflow Fraction	-	1														
Downstream Cell Number	-	1														
Surface Area	km2	55.77														
Mean Width of Flow Pt	km	10.00														
Number of Tanks in Series	-	1.0														
Minimum Depth for Releases	cm	15														
Release 1 Series Name	-	IRRIG														
Release 2 Series Name	-															
Outflow Series Name	-	TO_A1														
Depth Series Name	-	A2_DEPTH														
Outflow Control Depth	cm	8														
Outflow Weir Depth	cm	8														
Outflow Coefficient - Exponent	-	1.5														
Outflow Coefficient - Intercept	-	8														
Bypass Depth	cm	8														
Maximum Inflow	hm3/day	7.829														
Maximum Outflow	hm3/day	7.829														
Inflow Seepage Rate	(cm/d) / cm	0.000778														
Inflow Seepage Control Elev	cm	6														
Inflow Seepage Conc	ppb	100														
Outflow Seepage Rate	(cm/d) / cm	0.75														
Outflow Seepage Control Elev	cm	1														
Max Outflow Seepage Conc	ppb	0.75														
Seepage Recycle to Cell Number	-	1														
Seepage Recycle Fraction	-	0.75														
Seepage Discharge Fraction	-	0.75														
Initial Water Column Conc	ppb	30														
Initial P Storage Per Unit Area	mg/m2	375														
Initial Water Column Depth	cm	200														
C0 = Conc at 0 g/m2 P Storage	ppb	3														
C1 = Conc at 1 g/m2 P storage	ppb	150														
C2 = Conc at Half-Max Uptake	ppb	150														
K = Net Settling Rate at Steady State	m/yr	5.0														
Z1 = Saturated Uptake Depth	cm	40														
Z2 = Lower Penalty Depth	cm	100														
Z3 = Upper Penalty Depth	cm	400														
Output Variables			1	2	3	4	5	6	7	8	9	10	11	12	Overall	
Execution Time	sec/yr	1.56													1.56	
Run Date	-	10/10/06													10/10/06	
Starting Date for Simulation	-	01/01/65													01/01/65	
Starting Date for Output	-	05/01/65													05/01/65	
Ending Date	-	04/30/00													04/30/00	
Output Duration	days	12764													12764	
Cell Label	-	RES_A2													Total	
Downstream Cell Label	-	Outflow													-	
Network Simulation Name	-	EAASR_NET													EAASR_NE	
Simulation Type	-	Base													Base	
Surface Area	km2	55.77													55.77	
Mean Rainfall	cm/yr	128.19													128.2	
Mean ET	cm/yr	137.71													137.7	
Cell Inflow Volume	hm3/yr	460.7													460.7	
Cell Inflow Load	kg/yr	38540.5													38541	
Cell Inflow Conc	ppb	84													83.7	
Treated Outflow Volume	hm3/yr	232.9													232.9	
Treated Outflow Load	kg/yr	15677.5													15678	
Treated FWM Outflow Conc	ppb	67													67.3	
Upper Confidence Limit	ppb	#N/A													#N/A	
Lower Confidence Limit	ppb	#N/A													#N/A	
Total Outflow Volume - Bypass	hm3/yr	441.8													441.8	
Total Outflow Load - Bypass	kg/yr	30094.9													30094.9	
Total FWM Outflow Conc	ppb	68.1													68.1	
Bypass Load	kg/yr	0													0.0	
Bypass Load	%	0%													0.0	
Maximum Inflow	hm3/d	7.58													7.58	
Maximum Outflow	hm3/d	4.47													4.47	
Surface Load Reduction	kg/yr	22863													22863	
Load Trapped in Sediments	kg/yr	9195													9195	
Overall Load Reduction	%	22%													22%	
Lower Confidence Limit	%	#N/A													#N/A	
Upper Confidence Limit	%	#N/A													#N/A	
Daily Geometric Mean	ppb	70.8													#N/A	
Outflow Geo Mean - Composites	ppb	70.8													70.8	
Upper Confidence Limit	ppb	#N/A													#N/A	
Lower Confidence Limit	ppb	#N/A													#N/A	
Frequency Outflow Conc > 10 ppb	%	100%													100%	
Frequency Outflow Conc > 20 ppb	%	100%													100%	
Frequency Outflow Conc > 50 ppb	%	97%													100%	
Freq Outflow Volume > 10 ppb	%	53%													53%	
95th Percentile Outflow Conc	ppb	81.98													82	
Mean Biomass P Storage	mg/m2	425													425	
Storage Increase / Net Removal	%	1%													1%	
Net Storage Turnover Rate	1/yr	13.6													13.6	
Unit Area P Load	mg/m2-yr	691													691	
Unit Area P Removal	mg/m2-yr	165													165	
Mean Water Load	cm/d	2.3													2.3	
Max Water Load	cm/d	13.6													13.6	
Mean Depth	cm	258													258	
Minimum Depth	cm	1.0													1	
Maximum Depth	cm	430.6													431	
Frequency Depth < 10 cm	%	3%													2.6%	
Flow/Width	m2/day	126													126.1	
HRT Days	days	113.9													113.9	
Mean Velocity	cm/sec	0.06													0.06	
Seepage Outflow / Total Outflow	%	2%													4%	
Release 1 Outflow Volume	hm3/yr	208.92													208.9	
Release 2 Outflow Volume	hm3/yr	0.00													0.0	
95th Percentile Outflow Volume	hm3/d	2.3													2.3	
95th Percentile Outflow Load	kg/d	152.2													152.2	
Simulated / Specified Mean Depth	%	99%													1.0	
Release 1 Demand Met	%	97%													1.0	
Release 2 Demand Met	%	#N/A													#N/A	
Outflow Demand Met	%	100%													1.0	
Range Check - Mean Depth	-	10.00													0	
Range Check - Freq Depth < 10 cm	-	3%													1	
Range Check - Flow/Width	-	126													0	
Range Check - Inflow Conc	-	84													0	
Range Check - Outflow Conc	-	67													0	
Water Balance Error	%	0.00%													0.00%	
Mass Balance Error	%	0.00%													0.00%	
Warning or Error Messages	-	Cell 1 Freq 2 < 10 cm out of calib. range for RES_3. 0 vs. 0 - 0%														1



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	STAS4	STA-3/4 and the new EAASR STA											
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area											
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics											
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 100 ppb											
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 11250											
Integration Steps Per Day	-	4												
Number of Iterations	-	3												
Output Variable	-	Mean	Lower CL	Upper CL	Diagnostics									
Output Averaging Interval	days	30	FWM Outflow C (ppb)	11.9	#N/A	#N/A	H2O Balance Error Mean & Max	0.0%	0.0%					
Inflow Conc. Scale Factor	-	1	GM Outflow C (ppb)	9.2	#N/A	#N/A	Mass Balance Error Mean & Max	0.0%	0.0%					
Rainfall P Conc	ppb	10	Load Reduction %	86%	#N/A	#N/A	Iterations & Convergence	3	3					
Atmospheric P Load (Dry)	mg/m2-yr	20	Bypass Load (%)	0.0%			Warning/Error Messages	19						
Cell Number ->		1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	
Vegetation Type	->	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	
Inflow Fraction	-	0.23441798	0.1955713	0.164732	0.13497	0.13497	0.13497	0.13497	0.13497	0.13497	0.13497	0.13497	0.13497	
Downstream Cell Number	-	2	4	6	8	10	12	14	16	18	20	22	24	
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	6.07	9.11	6.07	9.11	6.07	9.11	
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	
Minimum Depth for Releases	cm													
Release 1 Series Name	-													
Release 2 Series Name	-													
Outflow Series Name	-													
Depth Series Name	-													
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Outflow Weir Depth	cm													
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	
Bypass Depth	cm													
Maximum Inflow	hm3/day													
Maximum Outflow	hm3/day													
Inflow Seepage Rate	(cm/d) / cm													
Inflow Seepage Control Elev	cm													
Inflow Seepage Conc	ppb													
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		
Outflow Seepage Control Elev	cm	67												
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	
Seepage Recycle to Cell Number	-	1	3	5	7	9	11	13	15	17	19	21	23	
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Seepage Discharge Fraction	-													
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	33.51	35.04	36.29	37.98	39.29	41.27	42.40	43.82	45.03	46.82	47.81	49.22	49.22
Run Date	-	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label	-	1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Net
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	6.07	9.11	6.07	9.11	6.07	9.11	112.49
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	213.3	207.5	177.7	174.0	148.7	141.8	122.6	120.4	122.6	120.4	122.6	120.4	308.6
Cell Inflow Load	kg/yr	17302.7	9476.7	14411.2	7955.7	12138.7	6104.7	9945.6	5957.0	9945.6	5957.0	9945.6	5957.0	73689
Cell Inflow Conc	ppb	81	46	81	46	81	43	81	49	81	49	81	49	81.1
Treated Outflow Volume	hm3/yr	207.5	206.8	174.0	173.5	141.8	141.4	120.4	120.0	120.4	120.0	120.4	120.0	880.7
Treated FWM Outflow Conc	kg/yr	9476.7	2455.6	7955.7	2075.8	6104.7	1772.5	5957.0	1403.6	5957.0	1403.6	5957.0	1403.6	10495
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	207.5	206.8	174.0	173.5	141.8	141.4	120.4	120.0	120.4	120.0	120.4	120.0	880.7
Total Outflow Load + Bypass	kg/yr	9476.7	2455.6	7955.7	2075.8	6104.7	1772.5	5957.0	1403.6	5957.0	1403.6	5957.0	1403.6	10495
Total FWM Outflow Conc	ppb	45.7	11.8	45.7	12.0	43.1	12.5	49.5	11.7	49.5	11.7	49.5	11.7	11.9
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Conc	ppb	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0.0
Maximum Inflow	hm3/d	2.72	2.67	2.26	2.23	1.91	1.86	1.56	1.54	1.56	1.54	1.56	1.54	11.57
Maximum Outflow	hm3/d	2.67	2.65	2.23	2.23	1.86	1.86	1.54	1.53	1.54	1.53	1.54	1.53	11.34
Outflow Load Reduction	kg/yr	7826	7041	6455	5880	6034	4332	3989	4553	3989	4553	3989	4553	63195
Load Trapped in Sediments	kg/yr	7824	7490	6555	6273	5764	4631	3084	4858	4034	4858	4034	4858	65215
Overall Load Reduction	%	45%	74%	45%	74%	50%	71%	40%	76%	40%	76%	40%	76%	95%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	38.8	7.7	38.1	7.8	38.5	8.0	42.3	7.5	42.3	7.5	42.3	7.5	#N/A
Outflow Geo Mean - Composites	ppb	40.4	9.1	40.6	9.2	38.6	9.9	44.2	9.1	44.2	9.1	44.2	9.1	9.2
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	46%	100%	47%	100%	58%	100%	47%	100%	47%	100%	47%	47%
Frequency Outflow Conc > 20 ppb	%	98%	0%	99%	0%	99%	1%	100%	0%	100%	0%	100%	0%	7%
Frequency Outflow Conc > 50 ppb	%	24%	0%	24%	0%	18%	0%	39%	0%	39%	0%	39%	0%	0%
Freq Outflow Volume > 10 ppb	%	100%	66%	100%	67%	100%	72%	100%	66%	100%	66%	100%	66%	67%
95th Percentile Outflow Conc	ppb	57.86	15.95	57.98	16.23	54.61	16.94	62.35	15.53	62.35	15.53	62.35	15.53	16
Mean Biomass P Storage	mg/m2	1999	532	2002	537	1884	521	2087	535	2087	535	2087	535	1195
Storage Increase / Net Removal	%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Net Storage Turnover Rate	1/yr	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	17.0
Unit Area P Load	mg/m2-yr	1407	671	1401	679	1263	684	1638	654	1638	654	1638	654	

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	STA34	STA-34 and the new EAASR STA												
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area												
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics												
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 100 ppb												
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 6000												
Integration Steps Per Day	-	4													
Number of Iterations	-	3													
Output Averaging Interval	days	30													
Inflow Conc. Scale Factor	-	1													
Rainfall P Conc	ppb	10													
Atmospheric P Load (Dry)	mg/m2-yr	20													
Cell Number ->			1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	
Vegetation Type	->	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3
Inflow Fraction	-	0.2891855	0.24113575	0.203111	0.089755	0.089755	0.089755	0.089755	0.089755	0.089755	0.089755	0.089755	0.089755	0.089755	0.089755
Downstream Cell Number	-	2	4	6	8	10	12	14	16	18	20	22	24	26	28
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	3.24	4.86	3.24	4.86	3.24	4.86	3.24	4.86
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Minimum Depth for Releases	cm														
Release 1 Series Name	-														
Release 2 Series Name	-														
Outflow Series Name	-														
Depth Series Name	-														
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	40
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day														
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		0.0035	
Outflow Seepage Control Elev	cm	67													
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20	20
Seepage Recycle to Cell Number	-	1	3	5	7	9	11	13	15	17	19	21	23	25	27
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55	15
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60	60
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3	3
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22	22
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300	300
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	40
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100	100
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200	200
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	31.28	32.68	33.85	35.35	36.54	38.04	39.37	40.99	42.29	43.82	44.95	46.48	48.48	101/006
Run Date	-	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label			1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	3.24	4.86	3.24	4.86	3.24	4.86	3.24	4.86
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17
Cell Inflow Volume	hm3/yr	283.1	258.3	218.1	215.3	184.5	178.5	80.5	78.5	80.5	78.5	80.5	78.5	80.5	78.5
Cell Inflow Load	kg/yr	21333.9	12954.7	17768.7	10683.7	14966.8	8461.1	6540.1	4303.8	6540.1	4303.8	6540.1	4303.8	6540.1	4303.8
Cell Inflow Conc	ppb	81	50	81	51	81	48	81	54	81	54	81	54	81	54
Treated Outflow Volume	hm3/yr	256.9	256.0	215.3	214.8	176.5	176.2	79.5	79.3	79.5	79.3	79.5	79.3	79.5	79.3
Treated FWM Outflow Conc	kg/yr	12954.7	3813.0	10683.7	3247.0	8461.1	2781.3	4303.8	1197.7	4303.8	1197.7	4303.8	1197.7	4303.8	1197.7
Upper Confidence Limit	ppb	15	61	15	15	15	15	15	15	15	15	15	15	15	15
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Load + Bypass	hm3/yr	256.9	256.0	215.3	214.8	176.5	176.2	79.5	79.3	79.5	79.3	79.5	79.3	79.5	79.3
Total Outflow Conc	kg/yr	12954.7	3813.0	10683.7	3247.0	8461.1	2781.3	4303.8	1197.7	4303.8	1197.7	4303.8	1197.7	4303.8	1197.7
Total FWM Outflow Conc	ppb	50.4	15.0	50.5	15.1	47.9	15.8	54.1	15.1	54.1	15.1	54.1	15.1	54.1	15.1
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Bypass Load	ppb	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Maximum Inflow	hm3/d	3.29	3.29	2.76	2.76	2.30	2.30	1.01	1.01	1.01	1.01	1.01	1.01	1.01	1.01
Maximum Outflow	hm3/d	3.29	3.28	2.76	2.75	2.30	2.30	1.01	1.01	1.01	1.01	1.01	1.01	1.01	1.01
Surface Load Reduction	kg/yr	8379	9142	6895	7627	6506	5680	2236	3106	2236	3106	2236	3106	2236	3106
Load Trapped in Sediments	kg/yr	8321	9580	6973	8020	6182	5979	2263	3269	2263	3269	2263	3269	2263	3269
Overall Load Reduction	%	39%	71%	39%	70%	43%	67%	34%	72%	34%	72%	34%	72%	34%	72%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	42.9	9.7	43.2	9.8	42.6	10.1	46.3	9.5	46.3	9.5	46.3	9.5	46.3	9.5
Outflow Geo Mean - Composites	ppb	44.7	11.4	44.8	11.6	43.0	12.3	48.7	12.1	48.7	12.1	48.7	12.1	48.7	12.1
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	68%	100%	70%	100%	75%	100%	76%	100%	76%	100%	76%	100%	71%
Frequency Outflow Conc > 20 ppb	%	100%	6%	100%	7%	100%	8%	100%	5%	100%	5%	100%	5%	100%	32%
Frequency Outflow Conc > 50 ppb	%	43%	0%	42%	0%	34%	0%	54%	0%	54%	0%	54%	0%	54%	7%
Freq Outflow Volume > 10 ppb	%	100%	82%	100%	83%	100%	86%	100%	85%	100%	85%	100%	85%	100%	84%
95th Percentile Outflow Conc	ppb	63.39	20.36	63.55	20.64	60.45									

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	STA34	STA-3/4 and the new EAASR STA											
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area											
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics											
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 100 ppb											
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 1800											
Integration Steps Per Day	-	4												
Number of Iterations	-	3												
Output Variable	-	Mean	Lower Cl	Upper Cl	Diagnostics									
Output Averaging Interval	days	30	FWM Outflow C (ppb)	19.2	#N/A	#N/A	H2O Balance Error Mean & Max	0.0%	0.0%					
Inflow Conc. Scale Factor	-	10	GM Outflow C (ppb)	14.6	#N/A	#N/A	Mass Balance Error Mean & Max	0.0%	0.0%					
Rainfall P Conc	mg/m2-yr	20	Load Reduction %	77%	#N/A	#N/A	Iterations & Convergence	3	0.0%					
Atmospheric P Load (Dry)	mg/m2-yr	20	Bypass 1 Load (%)	0.0%			Warning/Error Messages	15						
Cell Number ->		1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	
Vegetation Type	-	EMG-3	SAV-3	EMG-3	SAV-3	EMG-3	SAV-3	EMG-3	SAV-3	EMG-3	SAV-3	EMG-3	SAV-3	
Inflow Fraction	-	0.355942206		0.29637575		0.249841		0.032726		0.032726		0.032726		
Downstream Cell Number	-	2	4	6	8	10	12	14	16	18	20	22	24	
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	0.97	1.46	0.97	1.46	0.97	1.46	
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	
Minimum Depth for Releases	cm													
Release 1 Series Name	-													
Release 2 Series Name	-													
Outflow Series Name	-													
Depth Series Name	-													
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Outflow Weir Depth	cm													
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	
Bypass Depth	cm													
Maximum Inflow	hm3/day													
Maximum Outflow	hm3/day													
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	
Inflow Seepage Control Elev	cm													
Outflow Seepage Conc	ppb													
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	
Seepage Recycle to Cell Number	-	1	3	5	7	9	11	13	15	17	19	21	23	
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Seepage Discharge Fraction	-													
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	
Z1 = Saturated Uptake Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	
Z2 = Lower Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	32.38	33.80	35.13	36.40	37.82	39.15	41.44	42.83	44.13	45.40	46.88	47.95	47.95
Run Date	-	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06	10/10/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Outflow
Downstream Cell Label	-	1B	2B	3B	4B	5B	6B	7B	8B	9B	10B	11B	12B	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	0.97	1.46	0.97	1.46	0.97	1.46	74.23
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	323.3	316.8	283.3	285.4	226.8	218.7	29.7	28.4	29.7	28.4	29.7	28.4	908.6
Cell Inflow Load	kg/yr	26221.2	17349.0	21839.2	14557.5	16395.4	11465.6	2411.5	1715.2	2411.5	1715.2	2411.5	1715.2	73690
Cell Inflow Conc	ppb	81	55	81	55	81	52	81	58	81	58	81	58	81.1
Treated Outflow Volume	hm3/yr	316.9	314.8	285.4	284.9	218.7	218.3	29.4	29.4	29.4	29.4	29.4	29.4	886.1
Treated FWM Outflow Conc	kg/yr	17349.0	5913.8	14557.5	5028.9	11465.6	4313.1	1715.2	572.8	1715.2	572.8	1715.2	572.8	16874
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	316.9	314.8	285.4	284.9	218.7	218.3	29.4	29.4	29.4	29.4	29.4	29.4	886.1
Total Outflow Load + Bypass	kg/yr	17349.0	5913.8	14557.5	5028.9	11465.6	4313.1	1715.2	572.8	1715.2	572.8	1715.2	572.8	16974.2
Total FWM Outflow Conc	ppb	54.7	18.8	54.8	19.0	52.4	19.8	58.3	19.5	58.3	19.5	58.3	19.5	19.2
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Conc	ppb	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0.0
Maximum Inflow	hm3/d	4.12	4.05	3.43	3.39	2.89	2.84	0.38	0.37	0.38	0.37	0.38	0.37	11.57
Maximum Outflow	hm3/d	4.05	4.04	3.39	3.39	2.84	2.83	0.37	0.37	0.37	0.37	0.37	0.37	11.38
Surface Load Reduction	kg/yr	8872	11435	7282	9529	6930	7153	696	1142	696	1142	696	1142	56716
Load Trapped in Sediments	kg/yr	8759	11859	7342	9922	6553	7452	707	1191	707	1191	707	1191	57582
Overall Load Reduction	%	34%	62%	33%	62%	39%	62%	29%	67%	29%	67%	29%	67%	77%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	46.7	12.2	46.9	12.3	46.5	12.7	49.6	11.8	49.6	11.8	49.6	11.8	#N/A
Outflow Geo Mean - Composites	ppb	45.7	14.2	46.9	14.4	47.1	15.3	52.6	15.9	52.6	15.9	52.6	15.9	14.6
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	80%	100%	81%	100%	84%	100%	88%	100%	88%	100%	88%	81%
Frequency Outflow Conc > 20 ppb	%	100%	27%	100%	28%	100%	31%	100%	31%	100%	31%	100%	31%	54%
Frequency Outflow Conc > 50 ppb	%	54%	0%	50%	0%	51%	0%	62%	0%	62%	0%	62%	0%	29%
Freq Outflow Volume > 10 ppb	%	100%	91%	100%	91%	100%	93%	100%	94%	100%	94%	100%	94%	92%
95th Percentile Outflow Conc	ppb	68.10	26.15	68.29	26.45	65.52	27.25	72.49	25.76	72.49	25.76	72.49	25.76	27
Mean Biomass P Storage	mg/m2	2238	843	2242	850	2142	838	2285	820	2285	820	2285	820	1492
Storage Increase / Net Removal	%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	0%
Net Storage Turnover Rate	1/yr	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	18.2
Unit Area P Load	mg/m2-yr	2132	1229	2123	1243	1914	1285							

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	A1	Compartment A-1											
Input Series Name	-	TS_A1	15,200 acres (from A8)											
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation											
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation											
Starting Date for Output	-	05/01/65												
Integration Steps Per Day	-	4												
Number of Iterations	-	0												
Output Averaging Interval	days	30												
Inflow Conc Scale Factor	-	1												
Rainfall P Conc	ppb	10												
Atmospheric P Load (Dry)	mg/m2-yr	20												
Cell Number -->		1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label	-->	RES_3												
Vegetation Type	-	1												
Inflow Fraction	-	1												
Downstream Cell Number	-	1												
Surface Area	km2	61.54												
Mean Width of Flow Pt	km	6.70												
Number of Tanks in Series	-	1.0												
Minimum Depth for Releases	cm	15												
Release 1 Series Name	-	IRRRIG												
Release 2 Series Name	-	TO_A2												
Outflow Series Name	-	TO_STA												
Depth Series Name	-	A1 DEPTH												
Outflow Control Depth	cm	6												
Outflow Weir Depth	cm	8												
Outflow Coefficient - Exponent	-	1.5												
Outflow Coefficient - Intercept	-	8												
Bypass Depth	cm	8												
Maximum Inflow	hm3/day	9.05233												
Maximum Outflow	hm3/day	9.05233												
Inflow Seepage Rate	(cm/d) / cm	0.00081												
Inflow Seepage Control Elev	cm	6												
Inflow Seepage Conc	ppb	100												
Outflow Seepage Rate	(cm/d) / cm	0.75												
Outflow Seepage Control Elev	cm	1												
Max Outflow Seepage Conc	ppb	0.75												
Seepage Recycle to Cell Number	-	1												
Seepage Recycle Fraction	-	0.75												
Seepage Discharge Fraction	-	105												
Initial Water Column Conc	ppb	525												
Initial P Storage Per Unit Area	mg/m2	150												
Initial Water Column Depth	cm	3												
C0 = Conc at 0 g/m2 P Storage	ppb	150												
C1 = Conc at 1 g/m2 P storage	ppb	5.0												
C2 = Conc at Half-Max Uptake	ppb	40												
K = Net Settling Rate at Steady State	m/yr	100												
Z1 = Saturated Uptake Depth	cm	400												
Z2 = Lower Penalty Depth	cm	400												
Z3 = Upper Penalty Depth	cm	400												
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.47												1.47
Run Date	-	10/10/06												10/10/06
Starting Date for Simulation	-	01/01/65												01/01/65
Starting Date for Output	-	05/01/65												05/01/65
Ending Date	-	04/30/00												04/30/00
Output Duration	days	12784												12784
Cell Label	-	1												Total
Downstream Cell Label	-	Outflow												-
Network Simulation Name	-	EAASR_NET												EAASR_NET
Simulation Type	-	Base												Base
Surface Area	km2	61.54												61.54
Mean Rainfall	cm/yr	130.73												130.7
Mean ET	cm/yr	135.34												135.3
Cell Inflow Volume	hm3/yr	717.8												717.8
Cell Inflow Load	kg/yr	89362.2												89362
Cell Inflow Conc	ppb	125												124.5
Treated Outflow Volume	hm3/yr	578.3												578.3
Treated Outflow Load	kg/yr	61128.4												61128
Treated FWM Outflow Conc	ppb	106												105.7
Upper Confidence Limit	ppb	#N/A												#N/A
Lower Confidence Limit	ppb	#N/A												#N/A
Total Outflow Volume - Bypass	hm3/yr	701.7												701.7
Total Outflow Load - Bypass	kg/yr	75325.4												75325.4
Total FWM Outflow Conc	ppb	107.3												107.3
Bypass Load	kg/yr	0												0.0
Bypass Load	%	0%												0.0
Maximum Inflow	hm3/d	11.90												11.90
Maximum Outflow	hm3/d	9.01												9.01
Surface Load Reduction	kg/yr	28234												28234
Load Trapped in Sediments	kg/yr	13999												13999
Overall Load Reduction	%	16%												16%
Lower Confidence Limit	%	#N/A												#N/A
Upper Confidence Limit	%	#N/A												#N/A
Daily Geometric Mean	ppb	67.1												67.1
Outflow Geo Mean - Composites	ppb	92.8												92.8
Upper Confidence Limit	ppb	#N/A												#N/A
Lower Confidence Limit	ppb	#N/A												#N/A
Frequency Outflow Conc > 10 ppb	%	100%												100%
Frequency Outflow Conc > 20 ppb	%	100%												100%
Frequency Outflow Conc > 50 ppb	%	83%												100%
Freq Outflow Volume > 10 ppb	%	82%												82%
95th Percentile Outflow Conc	ppb	253.89												254
Mean Biomass P Storage	mg/m2	561												561
Storage Increase / Net Removal	%	1%												1%
Net Storage Turnover Rate	1/yr	14.2												14.2
Unit Area P Load	mg/m2-yr	1452												1452
Unit Area P Removal	mg/m2-yr	227												227
Mean Water Load	cm/d	3.2												3.2
Max Water Load	cm/d	19.3												19.3
Mean Depth	cm	220												220
Minimum Depth	cm	1.0												1
Maximum Depth	cm	379.5												379
Frequency Depth < 10 cm	%	6%												5.6%
Flow/Width	m2/day	293												293.3
HRT Days	days	68.8												68.8
Mean Velocity	cm/sec	0.15												0.15
Seepage Outflow / Total Outflow	%	1%												2%
Release 1 Outflow Volume	hm3/yr	0.00												0.0
Release 2 Outflow Volume	hm3/yr	123.43												123.4
95th Percentile Outflow Volume	hm3/d	4.8												4.8
95th Percentile Outflow Load	kg/d	559.7												559.7
Simulated / Specified Mean Depth	%	99%												1.0
Release 1 Demand Met	%	#N/A												#N/A
Release 2 Demand Met	%	98%												1.0
Outflow Demand Met	%	100%												1.0
Range Check - Mean Depth	-	10.00												0
Range Check - Freq Depth < 10 cm	-	10.00												1
Range Check - Flow/Width	-	10.00												0
Range Check - Inflow Conc	-	10.00												0
Range Check - Outflow Conc	-	10.00												0
Water Balance Error	%	0.00%												0.00%
Mass Balance Error	%	0.00%												0.00%
Warning or Error Messages		Cell 1 Freq 2 < 10 cm out of calib. range for RES_3. 0 vs. 0 - 0%												1



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	A2	Compartment A-2												
Input Series Name	-	T5_A2	13,775 acres of effective area												
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation												
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent stwmm simulation												
Starting Date for Output	-	05/01/65													
Integration Steps Per Day	-	4													
Number of Iterations	-	0	Simulation Type:												
Output Averaging Interval	days	30	Output Variable			Mean	Lower.CL	Upper.CL	Diagnostics						
Inflow Conc Scale Factor	-	1	FWM Outflow C (ppb)			71.6	#N/A	#N/A	H2O Balance Error Mean & Max					0.0%	
Rainfall P Conc	ppb	10	GM Outflow C (ppb)			77.1	#N/A	#N/A	Mass Balance Error Mean & Max					0.0%	
Atmospheric P Load (Dry)	mg/m2-yr	20	Load Reduction (%)			22%	#N/A	#N/A	Iterations & Convergence					3	
			Bypass Load (%)			0.0%			Warning/Error Messages					1	
Cell Number -->			1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label	-->	RES_A2													
Vegetation Type	-->	RES_3													
Inflow Fraction	-	1													
Downstream Cell Number	-														
Surface Area	km2	55.77													
Mean Width of Flow Pt	km	10.00													
Number of Tanks in Series	-	1.0													
Minimum Depth for Releases	cm	15													
Release 1 Series Name	-	IRRIG													
Release 2 Series Name	-														
Outflow Series Name	-	TO_A1													
Depth Series Name	-	A2_DEPTH													
Outflow Control Depth	cm	6													
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	1.5													
Outflow Coefficient - Intercept	-	8													
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day	7.829													
Inflow Seepage Rate	(cm/d) / cm														
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.000778													
Outflow Seepage Control Elev	cm	6													
Max Outflow Seepage Conc	ppb	100													
Seepage Recycle to Cell Number	-	1													
Seepage Recycle Fraction	-	0.75													
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	90													
Initial P Storage Per Unit Area	mg/m2	375													
Initial Water Column Depth	cm	200													
C0 = Conc at 0 g/m2 P Storage	ppb	3													
C1 = Conc at 1 g/m2 P storage	ppb	150													
C2 = Conc at Half-Max Uptake	ppb														
K = Net Settling Rate at Steady State	m/yr	5.0													
Z1 = Saturated Uptake Depth	cm	40													
Z2 = Lower Penalty Depth	cm	100													
Z3 = Upper Penalty Depth	cm	400													
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.56													1.56
Run Date	-	10/10/06													10/10/06
Starting Date for Simulation	-	01/01/65													01/01/65
Starting Date for Output	-	05/01/65													05/01/65
Ending Date	-	04/30/00													04/30/00
Output Duration	days	12784													12784
Cell Label	-	RES_A2													Total
Downstream Cell Label	-	Outflow													-
Network Simulation Name	-	EAASR_NET													EAASR_NET
Simulation Type	-	Base													Base
Surface Area	km2	55.77													55.77
Mean Rainfall	cm/yr	128.19													128.2
Mean ET	cm/yr	137.71													137.7
Cell Inflow Volume	hm3/yr	460.7													460.7
Cell Inflow Load	kg/yr	42486.9													42487
Cell Inflow Conc	ppb	92													92.2
Treated Outflow Volume	hm3/yr	232.9													232.9
Treated Outflow Load	kg/yr	16674.4													16674
Treated FWM Outflow Conc	ppb	72													71.6
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Total Outflow Volume - Bypass	hm3/yr	441.8													441.8
Total Outflow Load - Bypass	kg/yr	33038.7													33038.7
Total FWM Outflow Conc	ppb	74.8													74.8
Bypass Load	kg/yr	0													0.0
Bypass Load	%	0%													0.0
Maximum Inflow	hm3/d	7.58													7.58
Maximum Outflow	hm3/d	4.47													4.47
Surface Load Reduction	kg/yr	25812													25812
Load Trapped in Sediments	kg/yr	10025													10025
Overall Load Reduction	%	22%													22%
Lower Confidence Limit	%	#N/A													#N/A
Upper Confidence Limit	%	#N/A													#N/A
Daily Geometric Mean	ppb	77.5													77.5
Outflow Geo Mean - Composites	ppb	77.1													77.1
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Frequency Outflow Conc > 10 ppb	%	100%													100%
Frequency Outflow Conc > 20 ppb	%	100%													100%
Frequency Outflow Conc > 50 ppb	%	97%													100%
Freq Outflow Volume > 10 ppb	%	53%													53%
95th Percentile Outflow Conc	ppb	99.91													100
Mean Biomass P Storage	mg/m2	472													472
Storage Increase / Net Removal	%	1%													1%
Net Storage Turnover Rate	1/yr	13.3													13.3
Unit Area P Load	mg/m2-yr	782													782
Unit Area P Removal	mg/m2-yr	180													180
Mean Water Load	cm/d	2.3													2.3
Max Water Load	cm/d	13.6													13.6
Mean Depth	cm	258													258
Minimum Depth	cm	1.0													1
Maximum Depth	cm	430.6													431
Frequency Depth < 10 cm	%	3%													2.6%
Flow Width	m2/day	126													126.1
HRT Days	days	113.9													113.9
Mean Velocity	cm/sec	0.06													0.06
Seepage Outflow / Total Outflow	%	2%													4%
Release 1 Outflow Volume	hm3/yr	208.92													208.9
Release 2 Outflow Volume	hm3/yr	0.00													0.0
95th Percentile Outflow Volume	hm3/d	2.3													2.3
95th Percentile Outflow Load	kg/d	157.0													157.0
Simulated / Specified Mean Depth	%	99%													1.0
Release 1 Demand Met	%	97%													1.0
Release 2 Demand Met	%	#N/A													#N/A
Outflow Demand Met	%	100%													1.0
Range Check - Mean Depth	-														0
Range Check - Freq Depth < 10 cm	-	10.00													1
Range Check - Flow Width	-														0
Range Check - Inflow Conc	-														0
Range Check - Outflow Conc	-														0
Water Balance Error	%	0.00%													0.00%
Mass Balance Error	%	0.00%													0.00%
Warning or Error Messages			Cell 1 Freq Z < 10 cm out of calib. range for RES_3. 0 vs. 0-0%												



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	STA34	STA-34 and the new EAASR STA											
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area											
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics											
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 150 ppb											
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 15,300											
Integration Steps Per Day	-	4												
Number of Iterations	-	3												
Output Variable	-	Mean	Lower CL				Upper CL				Diagnostics			
Output Averaging Interval	days	30	#N/A				#N/A				H2O Balance Error Mean & Max 0.0%			
Inflow Conc. Scale Factor	-	1	#N/A				#N/A				Mass Balance Error Mean & Max 0.0%			
Rainfall P Conc	ppb	10	#N/A				#N/A				Iterations & Convergence 3			
Atmospheric P Load (Dry)	mg/m2-yr	20	0.0%				0.0%				Warning/Error Messages 19			
Cell Number ->		1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	
Vegetation Type	->	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	
Inflow Fraction	-	0.204938462	0.17099237	0.143774	0.12026	0.10206	0.08621	0.07206	0.05926	0.04726	0.03626	0.02626	0.01726	
Downstream Cell Number	-	2	4	6	8	10	12	14	16	18	20	22	24	
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	8.26	12.39	8.26	12.39	8.26	12.39	
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	
Minimum Depth for Releases	cm													
Release 1 Series Name	-													
Release 2 Series Name	-													
Outflow Series Name	-													
Depth Series Name	-													
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Outflow Weir Depth	cm													
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	
Bypass Depth	cm													
Maximum Inflow	hm3/day													
Maximum Outflow	hm3/day													
Inflow Seepage Rate	(cm/d) cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	
Inflow Seepage Control Elev	cm													
Inflow Seepage Conc	ppb													
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	
Seepage Recycle to Cell Number	-	1	3	3	5	5	7	7	9	9	11	11	11	
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Seepage Discharge Fraction	-													
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	36.91	36.68	40.00	43.05	44.24	45.68	47.04	48.60	50.07	51.66	53.04	54.57	54.57
Run Date	-	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	134	134	134	134	134	134	134	134	134	134	134	134	134
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label	-	1B	2B	3B	4B	5B	6B	6B	6B	6B	6B	6B	6B	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	8.26	12.39	8.26	12.39	8.26	12.39	128.89
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	182.8	182.8	151.1	151.1	130.6	122.8	145.6	142.4	145.6	142.4	145.6	142.4	308.6
Cell Inflow Load	kg/yr	19151.7	9716.6	15951.1	8160.5	13435.8	6158.3	14971.4	8375.3	14971.4	8375.3	14971.4	8375.3	93453
Cell Inflow Conc	ppb	103	54	103	54	103	50	103	59	103	59	103	59	102.9
Treated Outflow Volume	hm3/yr	180.6	178.9	151.4	150.9	122.8	122.5	142.4	141.9	142.4	141.9	142.4	141.9	878.0
Treated FWM Outflow Conc	kg/yr	9716.6	2053.1	8160.5	1766.9	6158.3	1515.6	8375.3	1614.6	8375.3	1614.6	8375.3	1614.6	10240
Upper Confidence Limit	ppb	54	12	54	12	54	12	54	11	54	11	54	11	11.7
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	180.6	178.9	151.4	150.9	122.8	122.5	142.4	141.9	142.4	141.9	142.4	141.9	878.0
Total Outflow Load + Bypass	kg/yr	9716.6	2053.1	8160.5	1766.9	6158.3	1515.6	8375.3	1614.6	8375.3	1614.6	8375.3	1614.6	10240
Total FWM Outflow Conc	ppb	53.8	11.7	53.9	11.8	50.1	12.4	58.8	11.4	58.8	11.4	58.8	11.4	11.7
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Load	hm3/d	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0.0
Maximum Inflow	hm3/d	2.32	2.32	1.98	1.95	1.66	1.62	1.85	1.82	1.85	1.82	1.85	1.82	11.57
Maximum Outflow	hm3/d	2.32	2.31	1.95	1.94	1.62	1.61	1.82	1.82	1.82	1.82	1.82	1.82	11.31
Surface Load Reduction	kg/yr	9435	7624	7791	6374	7278	4643	6596	6761	6596	6761	6596	6761	83213
Load Trapped in Sediments	kg/yr	9358	8076	7840	6769	6847	4944	6601	7177	6601	7177	6601	7177	85168
Overall Load Reduction	%	49%	78%	49%	78%	54%	75%	44%	81%	44%	81%	44%	81%	39%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	46.0	7.7	46.3	7.8	45.6	7.9	50.6	7.4	50.6	7.4	50.6	7.4	#N/A
Outflow Geo Mean - Composites	ppb	47.5	8.9	47.6	9.1	44.8	9.7	52.0	8.7	52.0	8.7	52.0	8.7	8.9
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	44%	100%	46%	100%	53%	100%	41%	100%	41%	100%	41%	43%
Frequency Outflow Conc > 20 ppb	%	100%	1%	100%	1%	100%	1%	100%	0%	100%	0%	100%	0%	8%
Frequency Outflow Conc > 50 ppb	%	54%	0%	54%	0%	42%	0%	59%	0%	59%	0%	59%	0%	1%
Freq Outflow Volume > 10 ppb	%	100%	63%	100%	64%	100%	69%	100%	61%	100%	61%	100%	61%	63%
95th Percentile Outflow Conc	ppb	73.89	16.50	74.12	16.72	69.61	17.09	79.56	15.86	79.56	15.86	79.56	15.86	16
Mean Biomass P Storage	mg/m2	2391	574	2394	580	2239	556	2511	581	2511	581	2511	581	1391
Storage Increase / Net Removal	-	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	0%
Net Storage Turnover Rate	1/yr	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	16.6
Unit Area P Load	mg/m2-yr	1557	688	1551	697	1398	690	1813	676	1813	676	1813	676	725

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:													
Design Case Name	-	STA34	STA-34 and the new EAASR STA													
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area													
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics													
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 150 ppb													
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 9,900													
Integration Steps Per Day	-	4														
Number of Iterations	-	3														
Output Averaging Interval	days	30														
Inflow Conc. Scale Factor	-	1														
Rainfall P Conc	ppb	10														
Atmospheric P Load (Dry)	mg/m2-yr	20														
Cell Number ->			1	2	3	4	5	6	7	8	9	10	11	12		
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B		
Vegetation Type	->		EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3		
Inflow Fraction		0.24693775	0.20559242	0.173145	0.124839	0.124839	0.124839	0.124839	0.124839	0.124839	0.124839	0.124839	0.124839	0.124839		
Downstream Cell Number	-	2	4	6	8	10	12	14	16	18	20	22	24	26		
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	5.34	8.02	5.34	8.02	5.34	8.02	5.34		
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33		
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0		
Minimum Depth for Releases	cm															
Release 1 Series Name																
Release 2 Series Name																
Outflow Series Name																
Depth Series Name																
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40		
Outflow Weir Depth	cm															
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4		
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1		
Bypass Depth	cm															
Maximum Inflow	hm3/day															
Maximum Outflow	hm3/day															
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784		
Inflow Seepage Control Elev	cm															
Inflow Seepage Conc	ppb															
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		0.0035		
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	40		
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20		
Seepage Recycle to Cell Number	-	1	3	3	5	5	7	7	9	9	11	11	13	13		
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5		
Seepage Discharge Fraction	-															
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55		
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400		
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60		
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3		
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22		
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300		
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8		
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40		
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100		
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200		
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall	
Execution Time	sec/yr	34.22	35.69	37.42	38.91	40.56	43.19	44.67	45.80	47.27	48.11	50.02	51.57	51.57	1009/06	
Run Date	-	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	1009/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	
Ending Date for Simulation	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	
Output Duration	days															
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total	
Downstream Cell Label			1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Outflow	
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	5.34	8.02	5.34	8.02	5.34	8.02	5.34	107.02	
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0	
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2	
Cell Inflow Volume	hm3/yr	22.42	21.84	18.63	18.07	15.73	14.84	11.24	11.15	11.34	11.15	11.34	11.15	11.34	308.6	
Cell Inflow Load	kg/yr	23064.0	13000.5	19209.7	10918.2	16190.5	8365.0	11666.3	7182.5	11666.3	7182.5	11666.3	7182.5	11666.3	93463	
Cell Inflow Conc	ppb	103	60	103	60	103	56	103	64	103	64	103	64	103	102.9	
Treated Outflow Volume	hm3/yr	218.4	216.6	183.0	182.5	149.4	149.0	111.5	111.1	111.5	111.1	111.5	111.1	111.5	881.6	
Treated FWM Outflow Conc	ppb	13000.5	3179.3	10918.2	2713.3	8365.0	2311.4	7182.5	1609.6	7182.5	1609.6	7182.5	1609.6	7182.5	13033	
Upper Confidence Limit	ppb	60	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	
Lower Confidence Limit	ppb	60	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	
Total Outflow Volume + Bypass	hm3/yr	218.4	216.6	183.0	182.5	149.4	149.0	111.5	111.1	111.5	111.1	111.5	111.1	111.5	881.6	
Total Outflow Load + Bypass	kg/yr	3179.3	3179.3	10918.2	2713.3	8365.0	2311.4	7182.5	1609.6	7182.5	1609.6	7182.5	1609.6	7182.5	13032.7	
Total FWM Outflow Conc	ppb	59.5	14.7	59.6	14.9	56.0	15.5	64.4	14.5	64.4	14.5	64.4	14.5	64.4	14.8	
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0.0	
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0.0	
Maximum Inflow	hm3/d	2.86	2.80	2.38	2.35	2.00	1.96	1.44	1.42	1.44	1.42	1.44	1.42	1.44	11.57	
Maximum Outflow	hm3/d	2.80	2.79	2.35	2.34	1.96	1.95	1.42	1.42	1.42	1.42	1.42	1.42	1.42	11.34	
Surface Load Reduction	kg/yr	10064	9821	8291	8205	7816	6054	4484	5573	4484	5573	4484	5573	4484	80420	
Load Trapped in Sediments	kg/yr	9926	10263	8318	8601	7331	6355	4489	5943	4489	5943	4489	5943	4489	81789	
Overall Load Reduction	%	44%	76%	42%	75%	49%	72%	39%	78%	39%	78%	39%	78%	39%	96%	
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	
Daily Geometric Mean	ppb	51.0	9.5	51.3	9.6	50.5	9.9	55.6	9.3	55.6	9.3	55.6	9.3	55.6	#N/A	
Outflow Geo Mean - Composites	ppb	52.5	11.1	52.7	11.3	50.0	12.0	57.4	11.2	57.4	11.2	57.4	11.2	57.4	11.3	
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	
Frequency Outflow Conc > 10 ppb	%	100%	63%	100%	64%	100%	73%	100%	66%	100%	66%	100%	66%	100%	66%	
Frequency Outflow Conc > 20 ppb	%	100%	7%	100%	8%	100%	9%	100%	6%	100%	6%	100%	6%	100%	6%	
Frequency Outflow Conc > 50 ppb	%	50%	0%	60%	0%	57%	0%	72%	0%	72%	0%	72%	0%	72%	0%	
Freq Outflow Volume > 10 ppb	%	100%	80%	100%	80%	100%	83%	100%	80%	100%	80%	100%	80%	100%	81%	
95th Percentile Outflow Conc	ppb	80.36	21.19	80.56	21.47	76.58	22.23	87.00	20.45	87.00	20.45	87.00	20.45	87.00	21.19	
Mean Biomass P Storage	mg/m2	2536	730	2540	737	2397	715	2638	731	2638	731	2638	731	2638	1547	
Storage																

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	A1	Compartment A-1												
Input Series Name	-	TS_A1	15,200 acres (from A8)												
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation												
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation												
Starting Date for Output	-	05/01/65													
Integration Steps Per Day	-	4	Simulation Type:												
Number of Iterations	-	0	Output Variable	Mean	Lower.CL	Upper.CL	Diagnostics								
Output Averaging Interval	days	30	FWM Outflow C (ppb)	134.4	#N/A	#N/A	H2O Balance Error Mean & Max	0.0%	0.0%						
Inflow Conc Scale Factor	-	1	GM Outflow C (ppb)	111.8	#N/A	#N/A	Mass Balance Error Mean & Max	0.0%	0.0%						
Rainfall P Conc	ppb	10	Load Reduction (%)	16%	#N/A	#N/A	Iterations & Convergence								
Atmospheric P Load (Dry)	mg/m2-yr	20	Bypass Load (%)	0.0%			Warning/Error Messages								
Cell Number -->	-	1	2	3	4	5	6	7	8	9	10	11	12		
Cell Label	-->	RES_3													
Vegetation Type	-	1													
Inflow Fraction	-	1													
Downstream Cell Number	-														
Surface Area	km2	61.54													
Mean Width of Flow Pt	km	6.70													
Number of Tanks in Series	-	1.0													
Minimum Depth for Releases	cm	15													
Release 1 Series Name	-	IRRIG													
Release 2 Series Name	-	TO_A2													
Outflow Series Name	-	TO_STA													
Depth Series Name	-	A1 DEPTH													
Outflow Control Depth	cm														
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	1.5													
Outflow Coefficient - Intercept	-	8													
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day	9.05233													
Inflow Seepage Rate	(cm/d) / cm														
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.00081													
Outflow Seepage Control Elev	cm	6													
Max Outflow Seepage Conc	ppb	100													
Seepage Recycle to Cell Number	-	1													
Seepage Recycle Fraction	-	0.75													
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	105													
Initial P Storage Per Unit Area	mg/m2	525													
Initial Water Column Depth	cm	150													
C0 = Conc at 0 g/m2 P Storage	ppb	3													
C1 = Conc at 1 g/m2 P storage	ppb	150													
C2 = Conc at Half-Max Uptake	ppb														
K = Net Settling Rate at Steady State	m/yr	5.0													
Z1 = Saturated Uptake Depth	cm	40													
Z2 = Lower Penalty Depth	cm	100													
Z3 = Upper Penalty Depth	cm	400													
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.59													1.59
Run Date	-	10/09/06													10/09/06
Starting Date for Simulation	-	01/01/65													01/01/65
Starting Date for Output	-	05/01/65													05/01/65
Ending Date	-	04/30/00													04/30/00
Output Duration	days	12784													12784
Cell Label	-	1													Total
Downstream Cell Label	-	Outflow													-
Network Simulation Name	-	EAASR_NET													EAASR_NET
Simulation Type	-	Base													Base
Surface Area	km2	61.54													61.54
Mean Rainfall	cm/yr	130.73													130.7
Mean ET	cm/yr	135.34													135.3
Cell Inflow Volume	hm3/yr	717.8													717.8
Cell Inflow Load	kg/yr	114562.8													114563
Cell Inflow Conc	ppb	160													159.6
Treated Outflow Volume	hm3/yr	578.3													578.3
Treated Outflow Load	kg/yr	77736.8													77737
Treated FWM Outflow Conc	ppb	134													134.4
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Total Outflow Volume - Bypass	hm3/yr	701.7													701.7
Total Outflow Load - Bypass	kg/yr	95947.1													95947.1
Total FWM Outflow Conc	ppb	136.7													136.7
Bypass Load	kg/yr	0													0.0
Bypass Load	%	0%													0.0
Maximum Inflow	hm3/d	11.90													11.90
Maximum Outflow	hm3/d	9.01													9.01
Surface Load Reduction	kg/yr	36826													36826
Load Trapped in Sediments	kg/yr	17376													17376
Overall Load Reduction	%	16%													16%
Lower Confidence Limit	%	#N/A													#N/A
Upper Confidence Limit	%	#N/A													#N/A
Daily Geometric Mean	ppb	105.3													#N/A
Outflow Geo Mean - Composites	ppb	111.8													111.8
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Frequency Outflow Conc > 10 ppb	%	100%													100%
Frequency Outflow Conc > 20 ppb	%	100%													100%
Frequency Outflow Conc > 50 ppb	%	84%													100%
Freq Outflow Volume > 10 ppb	%	82%													82%
95th Percentile Outflow Conc	ppb	302.53													303
Mean Biomass P Storage	mg/m2	710													710
Storage Increase / Net Removal	%	1%													1%
Net Storage Turnover Rate	1/yr	13.9													13.9
Unit Area P Load	mg/m2-yr	1862													1862
Unit Area P Removal	mg/m2-yr	282													282
Mean Water Load	cm/d	3.2													3.2
Max Water Load	cm/d	19.3													19.3
Mean Depth	cm	220													220
Minimum Depth	cm	1.0													1
Maximum Depth	cm	379.5													379
Frequency Depth < 10 cm	%	6%													5.6%
Flow/Width	m2/day	293													293.3
HRT Days	days	68.8													68.8
Mean Velocity	cm/sec	0.15													0.15
Seepage Outflow / Total Outflow	%	1%													2%
Release 1 Outflow Volume	hm3/yr	0.00													0.0
Release 2 Outflow Volume	hm3/yr	123.43													123.4
95th Percentile Outflow Volume	hm3/d	4.8													4.8
95th Percentile Outflow Load	kg/d	721.7													721.7
Simulated / Specified Mean Depth	%	99%													1.0
Release 1 Demand Met	%	#N/A													#N/A
Release 2 Demand Met	%	98%													1.0
Outflow Demand Met	%	100%													1.0
Range Check - Mean Depth	-														0
Range Check - Freq Depth < 10 cm	-	10.00													1
Range Check - Flow/Width	-														0
Range Check - Inflow Conc	-														0
Range Check - Outflow Conc	-														0
Water Balance Error	%	0.00%													0.00%
Mass Balance Error	%	0.00%													0.00%
Warning or Error Messages			Cell 1 Freq Z < 10 cm out of calib. range for RES_3. 0 vs. 0 - 0 %										1		



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	A2	Compartment A-2												
Input Series Name	-	T5_A2	13,775 acres of effective area												
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation												
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation												
Starting Date for Output	-	05/01/65													
Integration Steps Per Day	-	4													
Number of Iterations	-	0													
Output Averaging Interval	days	30													
Inflow Conc Scale Factor	-	1													
Rainfall P Conc	ppb	10													
Atmospheric P Load (Dry)	mg/m2-yr	20													
Simulation Type:			Mean	Lower CL	Upper CL	Diagnostics									
Output Variable			FWM Outflow C (ppb)	75.8	#N/A	#N/A	H2O Balance Error Mean & Max						0.0%	0.0%	
			GM Outflow C (ppb)	82.8	#N/A	#N/A	Mass Balance Error Mean & Max						0.0%	0.0%	
			Load Reduction %	23%	#N/A	#N/A	Iterations & Convergence						3	0.0%	
			Bypass Load (%)	0.0%			Warning/Error Messages						1		
Cell Number -->	-	1	2	3	4	5	6	7	8	9	10	11	12		
Cell Label	-->	RES_A2													
Vegetation Type	-->	RES_3													
Inflow Fraction	-	1													
Downstream Cell Number	-														
Surface Area	km2	55.77													
Mean Width of Flow Pt	km	10.00													
Number of Tanks in Series	-	1.0													
Minimum Depth for Releases	cm	15													
Release 1 Series Name	-	IRRRIG													
Release 2 Series Name	-														
Outflow Series Name	-	TO_A1													
Depth Series Name	-	A2_DEPTH													
Outflow Control Depth	cm	8													
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	1.5													
Outflow Coefficient - Intercept	-	8													
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day	7.829													
Inflow Seepage Rate	(cm/d) / cm														
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.000778													
Outflow Seepage Control Elev	cm	6													
Max Outflow Seepage Conc	ppb	100													
Seepage Recycle to Cell Number	-	1													
Seepage Recycle Fraction	-	0.75													
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	90													
Initial P Storage Per Unit Area	mg/m2	375													
Initial Water Column Depth	cm	200													
C0 = Conc at 0 g/m2 P Storage	ppb	3													
C1 = Conc at 1 g/m2 P storage	ppb	150													
C2 = Conc at Half-Max Uptake	ppb														
K = Net Settling Rate at Steady State	m/yr	5.0													
Z1 = Saturated Uptake Depth	cm	40													
Z2 = Lower Penalty Depth	cm	100													
Z3 = Upper Penalty Depth	cm	400													
Output Variables			1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.92													1.92
Run Date	-	10/09/06													10/09/06
Starting Date for Simulation	-	01/01/65													01/01/65
Starting Date for Output	-	05/01/65													05/01/65
Ending Date	-	04/30/00													04/30/00
Output Duration	days	12764													12764
Cell Label	-	RES_A2													Total
Downstream Cell Label	-	Outflow													-
Network Simulation Name	-	EAASR_NET													EAASR_NE
Simulation Type	-	Base													Base
Surface Area	km2	55.77													55.77
Mean Rainfall	cm/yr	128.19													128.2
Mean ET	cm/yr	137.71													137.7
Cell Inflow Volume	hm3/yr	460.7													460.7
Cell Inflow Load	kg/yr	46355.5													46356
Cell Inflow Conc	ppb	101													100.6
Treated Outflow Volume	hm3/yr	232.9													232.9
Treated Outflow Load	kg/yr	17645.9													17646
Treated FWM Outflow Conc	ppb	76													75.8
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Total Outflow Volume - Bypass	hm3/yr	441.8													441.8
Total Outflow Load - Bypass	kg/yr	35868.2													35868.2
Total FWM Outflow Conc	ppb	81.2													81.2
Bypass Load	kg/yr	0													0.0
Bypass Load %	%	0%													0.0
Maximum Inflow	hm3/d	7.58													7.58
Maximum Outflow	hm3/d	4.47													4.47
Surface Load Reduction	kg/yr	25710													25710
Load Trapped in Sediments	kg/yr	10824													10824
Overall Load Reduction	%	23%													23%
Lower Confidence Limit	%	#N/A													#N/A
Upper Confidence Limit	%	#N/A													#N/A
Daily Geometric Mean	ppb	83.9													#N/A
Outflow Geo Mean - Composites	ppb	82.8													82.8
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Frequency Outflow Conc > 10 ppb	%	100%													100%
Frequency Outflow Conc > 20 ppb	%	100%													100%
Frequency Outflow Conc > 50 ppb	%	97%													100%
Freq Outflow Volume > 10 ppb	%	53%													53%
95th Percentile Outflow Conc	ppb	117.13													117
Mean Biomass P Storage	mg/m2	518													518
Storage Increase / Net Removal	%	1%													1%
Net Storage Turnover Rate	1/yr	13.1													13.1
Unit Area P Load	mg/m2-yr	831													831
Unit Area P Removal	mg/m2-yr	194													194
Mean Water Load	cm/d	2.3													2.3
Max Water Load	cm/d	13.6													13.6
Mean Depth	cm	258													258
Minimum Depth	cm	1.0													1
Maximum Depth	cm	430.6													431
Frequency Depth < 10 cm	%	3%													2.6%
Flow/Width	m2/day	126													126.1
HRT Days	days	113.9													113.9
Mean Velocity	cm/sec	0.06													0.06
Seepage Outflow / Total Outflow	%	2%													4%
Release 1 Outflow Volume	hm3/yr	208.92													208.9
Release 2 Outflow Volume	hm3/yr	0.00													0.0
95th Percentile Outflow Volume	hm3/d	2.3													2.3
95th Percentile Outflow Load	kg/d	161.2													161.2
Simulated / Specified Mean Depth	%	99%													1.0
Release 1 Demand Met	%	97%													1.0
Release 2 Demand Met	%	#N/A													#N/A
Outflow Demand Met	%	100%													1.0
Range Check - Mean Depth	-														0
Range Check - Freq Depth < 10 cm	-	10.00													1
Range Check - Flow/Width	-														0
Range Check - Inflow Conc	-														0
Range Check - Outflow Conc	-														0
Water Balance Error	%	0.00%													0.00%
Mass Balance Error	%	0.00%													0.00%
Warning or Error Messages		Cell 1 Freq Z < 10 cm out of calib. range for RES_3. 0 vs. 0 - 0%													1



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	STA34	STA-34 and the new EAASR STA											
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area											
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics											
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 200 ppb											
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 17,750											
Integration Steps Per Day	-	4												
Number of Iterations	-	3												
Output Averaging Interval	days	30												
Inflow Conc. Scale Factor	-	1												
Rainfall P Conc	ppb	10												
Atmospheric P Load (Dry)	mg/m2-yr	20												
Cell Number ->			1	2	3	4	5	6	7	8	9	10	11	12
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B
Vegetation Type	->		EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3
Inflow Fraction	-	0.190293169		0.158492387		0.1335		0.112578		0.172578		0.172578		0.172578
Downstream Cell Number	-	2	4	4	4	4	4	4	4	4	4	4	4	4
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	9.58	14.37	9.58	14.37	9.58	14.37	9.58
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Minimum Depth for Releases	cm													
Release 1 Series Name	-													
Release 2 Series Name	-													
Outflow Series Name	-													
Depth Series Name	-													
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Outflow Weir Depth	cm													
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1
Bypass Depth	cm													
Maximum Inflow	hm3/day													
Maximum Outflow	hm3/day													
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Inflow Seepage Control Elev	cm													
Inflow Seepage Conc	ppb													
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		0.0035
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20
Seepage Recycle to Cell Number	-	1	3	3	3	5	5	7	7	9	9	11	11	11
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Seepage Discharge Fraction	-													
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	44.64	46.90	48.28	50.33	51.83	53.50	54.77	57.71	59.2	60.57	62.19	63.49	63.49
Run Date	-	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Cell Label		1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label		1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	9.58	14.37	9.58	14.37	9.58	14.37	138.80
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	172.9	187.4	144.0	140.4	121.3	113.5	158.8	153.1	158.8	153.1	158.8	153.1	908.6
Cell Inflow Load	21505.1	10493.1	17911.3	8815.1	15088.8	6567.0	1437.0	10545.6	1771.3	10545.6	1771.3	10545.6	1771.3	113012
Cell Inflow Conc	ppb	124	63	124	63	124	58	124	69	124	69	124	69	124.4
Treated Outflow Volume	hm3/yr	167.4	165.8	140.4	139.8	113.6	113.2	153.1	152.5	153.1	152.5	153.1	152.5	876.2
Treated FWM Outflow Conc	kg/yr	10453.1	1955.3	8815.1	1705.6	6567.0	1437.0	10545.6	1771.3	10545.6	1771.3	10545.6	1771.3	10452
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	167.4	165.8	140.4	139.8	113.6	113.2	153.1	152.5	153.1	152.5	153.1	152.5	876.2
Total Outflow Load + Bypass	kg/yr	10453.1	1955.3	8815.1	1705.6	6567.0	1437.0	10545.6	1771.3	10545.6	1771.3	10545.6	1771.3	10451.8
Total FWM Outflow Conc	ppb	62.7	12.0	62.8	12.2	57.8	12.7	68.9	11.6	68.9	11.6	68.9	11.6	11.9
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Load	hm3/d	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0.0
Maximum Inflow	hm3/d	2.20	2.15	1.83	1.81	1.54	1.50	2.00	1.96	2.00	1.96	2.00	1.96	11.57
Maximum Outflow	hm3/d	2.15	2.14	1.81	1.80	1.50	1.50	1.96	1.96	1.96	1.96	1.96	1.96	11.30
Surface Load Reduction	kg/yr	11012	8498	9096	7109	8520	5130	8957	8774	8957	8774	8957	8774	102561
Load Trapped in Sediments	kg/yr	10650	8950	9096	7506	7891	5433	8894	9259	8894	9259	8894	9259	104179
Overall Load Reduction	%	51%	91%	51%	91%	50%	78%	46%	83%	46%	83%	46%	83%	91%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	53.8	7.9	54.1	8.0	53.2	8.1	59.3	7.6	59.3	7.6	59.3	7.6	#N/A
Outflow Geo Mean - Composites	ppb	55.0	9.1	55.1	9.3	51.4	9.9	60.7	8.9	60.7	8.9	60.7	8.9	9.0
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	47%	100%	48%	100%	55%	100%	43%	100%	43%	100%	43%	46%
Frequency Outflow Conc > 20 ppb	%	100%	1%	100%	2%	100%	2%	100%	1%	100%	1%	100%	1%	12%
Frequency Outflow Conc > 50 ppb	%	60%	0%	60%	0%	58%	0%	74%	0%	74%	0%	74%	0%	1%
Freq Outflow Volume > 10 ppb	%	100%	65%	100%	66%	100%	70%	100%	62%	100%	62%	100%	62%	64%
95th Percentile Outflow Conc	ppb	90.75	17.27	91.08	17.58	85.07	17.97	97.72	16.59	97.72	16.59	97.72	16.59	17
Mean Biomass P Storage	mg/m2	2772	636	2776	643	2580	611	2916	647	2916	647	2916	647	1593
Storage Increase / Net Removal	%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	0%
Net Storage Turnover Rate	1/yr	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	16.5
Unit Area P Load	mg/m2-yr	1749	743	1741	753	1570	736	2035	734	2035	734	2035	734	814
Unit Area P Removal	mg/m2-yr	882	634	884	641	821	609	928	644	928	644	928	644	751
Mean Water Load	cm/d	3.8	3.2	3.8	3.3	3.5	3.5	4.5	2.9	4.5	2.9	4.5	2.9	1.8
Max Water Load	cm/d	17.9	15.3	17.8	15.4	16.1	16.8	20.8	13.7	20.8	13.7	20.8	13.7	8.3
Mean Depth	cm	54	52	54	51	46	47	53	54	53	54	53	54	52
Minimum Depth	cm	24.2	11.7	22.2	9.9	3.9	6.4	24.0	13.2	24.0	13.2	24.0	13.2	16
Maximum Depth	cm	89.0	83.0	88.8	81.7	74.4	74.4	87.5	87.5	87.5	87.5	87.5	87.5	85
Frequency Depth < 10 cm	%	0%	0%	0										

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	STA34	STA-34 and the new EAASR STA											
Input Series Name	-	TS_STA34	Inflows distributed uniformly based on area											
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics											
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 200 ppb											
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 12,350											
Integration Steps Per Day	-	4												
Number of Iterations	-	3												
Output Averaging Interval	days	30												
Inflow Conc. Scale Factor	-	1												
Rainfall P Conc	ppb	10												
Atmospheric P Load (Dry)	mg/m2-yr	20												
Cell Number ->			1	2	3	4	5	6	7	8	9	10	11	12
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B
Vegetation Type	->		EMG 3	SAV 3	EMG 3	SAV 3	EMG 3	SAV 3	EMG 3	SAV 3	EMG 3	SAV 3	EMG 3	SAV 3
Inflow Fraction	-	0.225969374		0.188123286		0.158458		0.142524		0.142524		0.142524		0.142524
Downstream Cell Number	-	2												
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	6.67	10.00	6.67	10.00	6.67	10.00	6.67
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Minimum Depth for Releases	cm													
Release 1 Series Name	-													
Release 2 Series Name	-													
Outflow Series Name	-													
Depth Series Name	-													
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Outflow Weir Depth	cm													
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1
Bypass Depth	cm													
Maximum Inflow	hm3/day													
Maximum Outflow	hm3/day													
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Inflow Seepage Control Elev	cm													
Inflow Seepage Conc	ppb													
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		0.0035
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20
Seepage Recycle to Cell Number	-	1	2	3	4	5	6	7	8	9	10	11	12	
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Seepage Discharge Fraction	-													
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	34.84	36.26	37.70	39.03	40.48	41.81	43.22	44.78	46.22	47.85	48.85	51.43	51.43
Run Date	-	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days													
Cell Label		1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label		1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	6.67	10.00	6.67	10.00	6.67	10.00	116.94
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	252.5	193.5	170.8	187.2	144.0	136.1	129.5	127.0	129.5	127.0	129.5	127.0	908.6
Cell Inflow Load	kg/yr	25252.5	13828.6	21259.8	11617.9	17907.4	8806.0	16106.7	9576.8	16106.7	9576.8	16106.7	9576.8	113013
Cell Inflow Conc	ppb	124	69	124	69	124	65	124	75	124	75	124	75	124.4
Treated Outflow Volume	hm3/yr	199.5	197.7	167.2	166.7	136.1	135.7	127.0	126.6	127.0	126.6	127.0	126.6	880.0
Treated FWM Outflow Conc	kg/yr	13828.6	2961.5	11617.9	2548.5	8806.0	2159.7	9576.8	1861.2	9576.8	1861.2	9576.8	1861.2	13273.2
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	199.5	197.7	167.2	166.7	136.1	135.7	127.0	126.6	127.0	126.6	127.0	126.6	880.0
Total Outflow Load + Bypass	kg/yr	13828.6	2961.5	11617.9	2548.5	8806.0	2159.7	9576.8	1861.2	9576.8	1861.2	9576.8	1861.2	13273.2
Total FWM Outflow Conc	ppb	69.3	15.1	69.5	15.3	64.7	15.9	75.4	14.7	75.4	14.7	75.4	14.7	15.1
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0
Bypass Conc	ppb	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Maximum Inflow	hm3/d	2.56	2.56	2.15	2.14	1.79	1.78	1.62	1.62	1.62	1.62	1.62	1.62	11.33
Maximum Outflow	hm3/d	2.56	2.56	2.15	2.14	1.79	1.78	1.62	1.62	1.62	1.62	1.62	1.62	11.33
Surface Load Reduction	kg/yr	11697	10847	9642	9069	9101	6646	6530	7716	6530	7716	6530	7716	99740
Load Trapped in Sediments	kg/yr	11469	11288	9611	9466	8438	6949	6487	8054	6487	8054	6487	8054	100643
Overall Load Reduction	%	46%	76%	42%	76%	51%	75%	41%	81%	41%	81%	41%	81%	35%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	59.5	9.8	59.9	9.9	59.1	10.1	65.2	9.5	65.2	9.5	65.2	9.5	#N/A
Outflow Geo Mean - Composites	ppb	60.7	11.3	61.0	11.5	57.4	12.2	66.6	11.2	66.6	11.2	66.6	11.2	11.4
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	63%	100%	66%	100%	73%	100%	63%	100%	63%	100%	63%	65%
Frequency Outflow Conc > 20 ppb	%	100%	9%	100%	10%	100%	12%	100%	9%	100%	9%	100%	9%	30%
Frequency Outflow Conc > 50 ppb	%	74%	0%	74%	0%	69%	0%	80%	0%	80%	0%	80%	0%	9%
Freq Outflow Volume > 10 ppb	%	100%	80%	100%	81%	100%	84%	100%	79%	100%	79%	100%	79%	80%
95th Percentile Outflow Conc	ppb	98.05	22.74	98.55	23.04	93.14	23.53	107.08	21.86	107.08	21.86	107.08	21.86	23
Mean Biomass P Storage	mg/m2	2930	803	2935	811	2759	782	3057	808	3057	808	3057	808	1761
Storage Increase / Net Removal	%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	0%
Net Storage Turnover Rate	1/yr	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	17.1
Unit Area P Load	mg/m2-yr	2076	980	2067	992	1863	987	2416	958	2416	958	2416	958	966
Unit Area P Removal	mg/m2-yr	933	800	934	808	878	779	973	805	973	805	973	805	862
Mean Water Load	cm/d	4.6	3.9	4.5	3.9	4.1	4.2	5.3	3.5	5.3	3.5	5.3	3.5	2.1
Max Water Load	cm/d	21.3	18.2	21.2	18.3	19.1	20.0	24.7	18.2	24.7	18.2	24.7	18.2	9.9
Mean Depth	cm	56	54	56	53	47	48	51	52	51	52	51	52	52
Minimum Depth	cm	24.8	15.5	23.0	13.5	8.2	6.7	24.4	14.6	24.4	14.6	24.4	14.6	17
Maximum Depth	cm	92.9	86.7	92.8	85.4	77.7	77.7	83.4	83.4	83.4	83.4	83.4	83.4	85
Frequency Depth < 10 cm	%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0			

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	STAS4	STA-3/4 and the new EAASR STA												
Input Series Name	-	TS_STA3/4	Inflows distributed uniformly based on area												
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics												
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 200 ppb												
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 7,800												
Integration Steps Per Day	-	4													
Number of Iterations	-	3													
Output Averaging Interval	days	30													
Inflow Conc. Scale Factor	-	1													
Rainfall P Conc	ppb	10													
Atmospheric P Load (Dry)	mg/m2-yr	20													
Cell Number ->			1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	
Vegetation Type	->		EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	
Inflow Fraction	-	0.268102696													
Downstream Cell Number	-	2	4	4	4	4	4	4	4	4	4	4	4	4	
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	4.21	6.32	4.21	6.32	4.21	6.32	4.21	
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33	
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	
Minimum Depth for Releases	cm														
Release 1 Series Name	-														
Release 2 Series Name	-														
Outflow Series Name	-														
Depth Series Name	-														
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4	
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1	
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day														
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		0.0035	
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20	
Seepage Recycle to Cell Number	-	1	3	3	3	5	5	7	7	9	9	11	11	11	
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55	
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400	
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60	
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3	
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22	
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300	
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100	
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200	
Output Variables			1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	38.10	41.01	42.51	44.01	45.80	47.01	48.57	50.21	52.59	54.01	55.76	58.08	58.08	
Run Date	-	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06	10/09/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label	-		1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	4.21	6.32	4.21	6.32	4.21	6.32	4.21	98.52
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	243.8	237.6	203.3	193.1	170.9	162.9	97.1	95.6	97.1	95.6	97.1	95.6	97.1	958.6
Cell Inflow Load	kg/yr	30298.3	17972.8	25235.0	15098.0	21255.8	11606.2	12074.7	7789.7	12074.7	7789.7	12074.7	7789.7	12074.7	113013
Cell Inflow Conc	ppb	124	76	124	76	124	71	124	81	124	81	124	81	124	124.4
Treated Outflow Volume	hm3/yr	237.6	235.7	199.1	198.6	162.9	162.6	95.6	95.3	95.6	95.3	95.6	95.3	95.6	882.8
Treated FWM Outflow Conc	kg/yr	17972.8	4478.2	15098.0	3825.4	11606.2	3254.0	7789.7	1787.7	7789.7	1787.7	7789.7	1787.7	7789.7	16821
Upper Confidence Limit	ppb	19	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	237.6	235.7	199.1	198.6	162.9	162.6	95.6	95.3	95.6	95.3	95.6	95.3	95.6	882.8
Total Outflow Load + Bypass	kg/yr	17972.8	4478.2	15098.0	3825.4	11606.2	3254.0	7789.7	1787.7	7789.7	1787.7	7789.7	1787.7	7789.7	16920.7
Total FWM Outflow Conc	ppb	75.6	19.0	75.8	19.3	71.2	20.0	81.5	18.8	81.5	18.8	81.5	18.8	19.2	19.2
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Conc	ppb	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0.0
Maximum Inflow	hm3/d	3.10	3.05	2.58	2.55	2.18	2.13	1.24	1.24	1.22	1.22	1.22	1.22	1.22	11.57
Maximum Outflow	hm3/d	3.05	3.03	2.55	2.55	2.13	2.12	1.22	1.22	1.22	1.22	1.22	1.22	1.22	11.35
Surface Load Reduction	kg/yr	12326	13495	10137	11273	9650	8352	4285	6002	4285	6002	4285	6002	96093	
Load Trapped in Sediments	kg/yr	12032	13921	10085	11671	8922	8656	4264	6216	4264	6216	4264	6216	96727	
Overall Load Reduction	%	41%	75%	40%	75%	45%	72%	35%	77%	35%	77%	35%	77%	35%	85%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	64.9	12.2	65.4	12.4	64.7	12.7	70.7	11.9	70.7	11.9	70.7	11.9	#N/A	#N/A
Outflow Geo Mean - Composites	ppb	66.4	14.1	66.6	14.4	63.3	15.2	72.3	14.5	72.3	14.5	72.3	14.5	14.4	#N/A
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	77%	100%	78%	100%	81%	100%	81%	100%	81%	100%	81%	78%	78%
Frequency Outflow Conc > 20 ppb	%	100%	27%	100%	28%	100%	33%	100%	25%	100%	25%	100%	25%	52%	52%
Frequency Outflow Conc > 50 ppb	%	80%	0%	80%	0%	77%	0%	84%	0%	84%	0%	84%	0%	28%	28%
Freq Outflow Volume > 10 ppb	%	100%	88%	100%	88%	100%	90%	100%	89%	100%	89%	100%	89%	89%	89%
95th Percentile Outflow Conc	ppb	106.82	29.55	107.17	30.04	101.49	30.95	116.07	28.69	116.07	28.69	116.07	28.69	30	30
Mean Biomass P Storage	mg/m2	3074	990	3090	1000	2917	974	3181	987	3181	987	3181	987	1936	1936
Storage Increase / Net Removal	-	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	-1%
Net Storage Turnover Rate	1/yr	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	11.1	34.9	17.7	17.7
Unit Area P Load	mg/m2-yr	2464	1273	2453	1289	2212	1301	2868	1233	2868	1233	2868	1233	1147	1147
Unit Area P Removal	mg/m2-yr	978	986	980	996	928	970	1013	984	1013	984	1013	984	982	982
Mean Water Load	cm/d	5.4	4.6	5.4	4.7	4.9	5.0	6.3	4.1	6.3	4.1	6.3	4.1	2.5	2.5
Max Water Load	cm/d	25.2	21.6	25.1	21.8	22.6	23.9	29.4	19.3	29.4	19.3	29.4	19.3	11.7	11.7
Mean Depth	cm	58	56	57	55	49	50	48	49	48	49	4			

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:															
Design Case Name	-	STA34_12_2	STA-3/4 and the new EAASR STA															
Input Series Name	-	TS_ST34	Inflow distributed uniformly based on area															
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics															
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 150 ppb															
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 18,100															
Integration Steps Per Day	-	4	Simulation Type: Base															
Number of Iterations	-	3	Output Variable															
Output Averaging Interval	days	365	Mean	Lower CL	Upper CL	Diagnostics						H2O Balance Error Mean & Max	0.0%	0.0%				
Inflow Conc Scale Factor	-	1	FWM Outflow C (ppb)	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	Mass Balance Error Mean & Max	0.0%	0.0%	
Rainfall P Conc	ppb	10	GM Outflow C (ppb)	10.3	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	Iterations & Convergence	3	0.0%	
Atmospheric P Load (Dry)	mg/m2-yr	20	Load Reduction %	89%	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	Warning/Error Messages	0		
			Bypass Load (%)	0.0%														
Cell Number -->			1	2	3	4	5	6	7	8	9	10	11	12				
Cell Label	-		1A	2B	3A	4B	5A	6B	7A	8B	9A	10B	11A	12B				
Vegetation Type	-		EMG 3	none	EMG 3	none	EMG 3	none	EMG 3	none	EMG 3	none	EMG 3	none				
Inflow Fraction	-	0.188370128		0.156889714		0.132151		0.174203		0.174203		0.174203		0.174203				
Downstream Cell Number	-	2	4	6	8	10	12											
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	9.77	14.66	9.77	14.66	9.77	14.66	9.77	14.66			
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33	3.33			
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0			
Minimum Depth for Releases	cm																	
Release 1 Series Name	-																	
Release 2 Series Name	-																	
Outflow Series Name	-																	
Depth Series Name	-																	
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	40			
Outflow Weir Depth	cm																	
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4	4			
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1	1			
Bypass Depth	cm																	
Maximum Inflow	hm3/day																	
Maximum Outflow	hm3/day																	
Inflow Seepage Rate	(cm/d) / cm																	
Inflow Seepage Control Elev	cm																	
Inflow Seepage Conc	ppb																	
Outflow Seepage Control Elev	cm	16	40	-67		-64		20	20	20	20	20	20	20	20			
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20	20			
Seepage Recycle to Cell Number	-	1	3	3	3	3	3	3	3	3	3	3	3	3	3			
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5			
Seepage Discharge Fraction	-																	
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55	15			
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615			
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60	60			
C0 = Conc at 0 g/m2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3	3			
C1 = Conc at 1 g/m2 P storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22	22			
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300	300			
K = Net Settling Rate at Steady State	m/yr	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7			
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	40			
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100	100			
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200	200			
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall				
Execution Time	sec/yr	18.23	19.64	20.46	21.17	21.94	22.70	23.44	24.23	25.19	26.18	27.23	28.25	28.25				
Run Date	-	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06	10/12/06			
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65			
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65			
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00			
Output Duration	days	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784			
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	6B	Total			
Downstream Cell Label	-	1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	6B	Outflow			
Network Simulation Name	-	none	none	none	none	none	none	none	none	none	none	none	none	none	none			
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base			
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	9.77	14.66	9.77	14.66	9.77	14.66	9.77	14.66			
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99			
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17			
Cell Inflow Volume	hm3/yr	171.2	155.7	142.6	139.0	120.1	112.4	104.4	104.4	104.4	104.4	104.4	104.4	104.4	104.4			
Cell Inflow Load	kg/yr	17093.3	8467.5	14662.5	7110.8	12349.8	5397.7	16279.3	8672.8	16279.3	8672.8	16279.3	8672.8	16279.3	8672.8			
Cell Inflow Conc	ppb	103	51	103	51	103	47	103	56	103	56	103	56	103	56			
Treated Outflow Volume	hm3/yr	165.7	164.1	139.0	138.5	112.4	112.0	154.6	153.9	154.6	153.9	154.6	153.9	154.6	153.9			
Treated Outflow Load	kg/yr	8467.5	1987.7	7110.8	1697.1	5320.7	1422.1	8672.8	1811.9	8672.8	1811.9	8672.8	1811.9	8672.8	1811.9			
Treated FWM Outflow Conc	ppb	51	12	51	12	47	13	56	12	56	12	56	12	56	12			
Upper Confidence Limit	ppb	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A			
Lower Confidence Limit	ppb	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A			
Total Outflow Volume + Bypass	hm3/yr	165.7	164.1	139.0	138.5	112.4	112.0	154.6	153.9	154.6	153.9	154.6	153.9	154.6	153.9			
Total Outflow Load + Bypass	kg/yr	8467.5	1987.7	7110.8	1697.1	5320.7	1422.1	8672.8	1811.9	8672.8	1811.9	8672.8	1811.9	8672.8	1811.9			
Total FWM Outflow Conc	ppb	51.1	12.1	51.2	12.3	47.3	12.7	56.1	11.8	56.1	11.8	56.1	11.8	56.1	11.8			
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
Bypass Load %	%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%			
Maximum Inflow	hm3/d	0.90	0.89	0.75	0.74	0.63	0.61	0.83	0.82	0.83	0.82	0.83	0.82	0.83	0.82			
Maximum Outflow	hm3/d	0.89	0.89	0.74	0.75	0.61	0.61	0.82	0.83	0.82	0.83	0.82	0.83	0.82	0.83			
Surface Load Reduction	kg/yr	9136	6480	7551	5414	7029	3899	7607	6861	7607	6861	7607	6861	7607	6861			
Load Trapped in Sediments	kg/yr	9107	6930	7629	5906	6622	4198	7633	7351	7633	7351	7633	7351	7633	7351			
Overall Load Reduction	%	52%	77%	52%	76%	57%	73%	47%	79%	47%	79%	47%	79%	47%	79%			
Lower Confidence Limit	%	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A	#/A			
Upper Confidence Limit	%	#/A	#/A	#/A</														

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:											
Design Case Name	-	STA34_19_2	STA-3/4 and the new EAASR STA											
Input Series Name	-	TS_ST34	Inflow distributed uniformly based on area											
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics											
Ending Date for Simulation	-	04/30/00	Lake Okeechobee deliveries at 150 ppb											
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 7.726											
Integration Steps Per Day	-	4	Simulation Type: Base											
Number of Iterations	-	3	Output Variable											
Output Averaging Interval	days	365	Mean											
Inflow Conc Scale Factor	-	1	#N/A											
Rainfall P Conc	ppb	10	FWM Outflow C (ppb)											
Atmospheric P Load (Dry)	mg/m2-yr	20	GM Outflow C (ppb)											
			Load Reduction %											
			Bypass Load (%)											
			Diagnosics											
			H2O Balance Error Mean & Max											
			Mass Balance Error Mean & Max											
			Iterations & Convergence											
			Warning/Error Messages											
Cell Number -->			1	2	3	4	5	6	7	8	9	10	11	12
Cell Label	-		1A	2A	3A	4A	5A	6A	7A	8A	9A	10A	11A	12A
Vegetation Type	->		EMG 3	none	EMG 3	none	EMG 3	none	EMG 3	none	EMG 3	none	EMG 3	none
Inflow Fraction	-	0.268920486		0.223979926		0.188661		0.106156		0.106155		0.106156		0.106156
Downstream Cell Number	-	2	4	4	6	6	8	10	10	12	12	12	12	12
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	4.17	6.26	4.17	6.26	4.17	6.26	4.17
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
Minimum Depth for Releases	cm													
Release 1 Series Name	-													
Release 2 Series Name	-													
Outflow Series Name	-													
Depth Series Name	-													
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Outflow Weir Depth	cm													
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1
Bypass Depth	cm													
Maximum Inflow	hm3/day													
Maximum Outflow	hm3/day													
Inflow Seepage Rate	(cm/d) / cm													
Inflow Seepage Control Elev	cm													
Inflow Seepage Conc	ppb													
Outflow Seepage Control Elev	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		
Max Outflow Seepage Conc	ppb	16	40	-67		-64		20		20		20		20
Seepage Recycle to Cell Number	-	1	1	1	1	1	1	1	1	1	1	1	1	1
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Seepage Discharge Fraction	-													
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60
C0 = Conc at 0 g/m2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3
C1 = Conc at 1 g/m2 P storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300
K = Net Settling Rate at Steady State	m/yr	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7	16.8	43.7	16.8
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200
Output Variables	Units	1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	19.16	19.84	20.52	21.34	22.36	23.38	24.26	25.28	26.30	27.26	28.53	29.35	29.35
Run Date	-	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Starting Date for Output	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784
Cell Label	-	1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label	-	1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	none
Network Simulation Name	-	none	none	none	none	none	none	none	none	none	none	none	none	none
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	4.17	6.26	4.17	6.26	4.17	6.26	98.22
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.00
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	244.5	238.5	203.6	199.9	171.5	163.5	96.5	95.0	96.5	95.0	96.5	95.0	905.1
Cell Inflow Load	kg/yr	25130.8	14794.9	20911.1	1242.2	17630.5	9577.4	9920.3	6352.0	9920.3	6352.0	9920.3	6352.0	93453
Cell Inflow Conc	ppb	103	62	103	62	103	59	103	67	103	67	103	67	102.8
Treated Outflow Volume	hm3/yr	238.5	236.6	199.9	199.3	163.5	163.2	95.0	94.8	95.0	94.8	95.0	94.8	883.3
Treated Outflow Load	kg/yr	14794.9	4450.1	12424.2	3795.6	9577.4	3207.4	6352.0	1775.7	6352.0	1775.7	6352.0	1775.7	16780
Treated FWM Outflow Conc	ppb	62	19	62	19	59	20	67	19	67	19	67	19	19.0
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	238.5	236.6	199.9	199.3	163.5	163.2	95.0	94.8	95.0	94.8	95.0	94.8	883.3
Total Outflow Load + Bypass	kg/yr	14794.9	4450.1	12424.2	3795.6	9577.4	3207.4	6352.0	1775.7	6352.0	1775.7	6352.0	1775.7	16780.1
Total FWM Outflow Conc	ppb	62.0	18.8	62.2	19.0	58.6	19.7	66.8	18.7	66.8	18.7	66.8	18.7	19.0
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Conc	ppb	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%
Maximum Inflow	hm3/d	1.28	1.27	1.06	1.06	0.90	0.88	0.50	0.50	0.50	0.50	0.50	0.50	4.75
Maximum Outflow	hm3/d	1.27	1.27	1.06	1.07	0.88	0.89	0.50	0.51	0.50	0.51	0.50	0.51	4.75
Surface Load Reduction	kg/yr	10336	10345	8507	8629	8053	6370	3568	4576	3568	4576	3568	4576	76673
Load Trapped in Sediments	kg/yr	10201	10770	8549	9020	7560	6669	3586	4785	3586	4785	3586	4785	77885
Overall Load Reduction	%	41%	70%	41%	69%	46%	67%	36%	72%	36%	72%	36%	72%	82%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	53.8	13.0	54.2	13.1	53.4	13.4	58.5	12.7	58.5	12.7	58.5	12.7	#N/A
Outflow Geo Mean - Composites	ppb	56.2	15.8	56.3	16.0	53.0	16.7	60.8	16.1	60.8	16.1	60.8	16.1	16.1
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	86%	100%	89%	100%	94%	100%	94%	100%	94%	100%	94%	92%
Frequency Outflow Conc > 20 ppb	%	100%	28%	100%	31%	100%	33%	100%	25%	100%	25%	100%	25%	58%
Frequency Outflow Conc > 50 ppb	%	64%	0%	64%	0%	58%	0%	78%	0%	78%	0%	78%	0%	28%
Freq Outflow Volume > 10 ppb	%	100%	90%	100%	90%	100%	92%	100%	91%	100%	91%	100%	91%	91%
95th Percentile Outflow Conc	ppb	79.64	25.72	79.86	26.09	75.38	26.68	85.17	25.26	85.17	25.26	85.17	25.26	26
Mean Biomass P Storage	mg/m2	2623	937	2628	946	2489	919	2717	939	2717	939	2717	939	1704
Storage Increase / Net Removal	%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%	0%	-1%
Net Storage Turnover Rate	1/yr	11.1	28.5	11.1	28.5	11.1	28.5	11.1	28.5	11.1	28.5	11.1	28.5	16.3
Unit Area P Load	mg/m2-yr	2043	1048	2035	1061	1835	1074	2379	1015	2379	1015	2379	1015	951
Unit Area P Removal	mg/m2-yr	829	763	831	770	787	748	860	765	860	765	860	765	793
Mean Water Load	cm/d	5.4	4.6	5.4	4.7	4.9	5.0	6.3	4.2	6.3	4.2	6.3	4.2	2.5
Max Water Load	cm/d	10.4	9.0	10.3	9.1	9.3	9.9	12.1	8.0	12.1	8.0	12.1	8.0	4.8
Mean Depth	cm	57	56	57	55	48	50	48	49	48	49	48	49	52
Minimum Depth	cm	41.6	37.6	41.2	36.8	32.9	31.8	37.9	34.3	37.9	34.3	37.9	34.3	37
Maximum Depth	cm	73.9	70.5	73.8	69.4	61.8	62.8	58.						

Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	A1	Compartment A-1												
Input Series Name	-	TS_A1	15,200 acres (from A8)												
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation												
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation												
Starting Date for Output	-	05/01/65													
Integration Steps Per Day	-	4													
Number of Iterations	-	0													
Output Averaging Interval	days	365													
Inflow Conc Scale Factor	-	1													
Rainfall P Conc	ppb	10													
Atmospheric P Load (Dry)	mg/m2-yr	20													
Simulation Type:			Mean	Lower CL	Upper CL	Diagnostics									
Output Variable			FWM Outflow C (ppb)	96.5	#N/A	#N/A	H2O Balance Error Mean & Max		0.0%	0.0%					
			GM Outflow C (ppb)	76.1	#N/A	#N/A	Mass Balance Error Mean & Max		0.0%	0.0%					
			Load Reduction %	21%	#N/A	#N/A	Iterations & Convergence		3	0.0%					
			Bypass Load (%)	0.0%			Warning/Error Messages		0						
Cell Number -->		1	2	3	4	5	6	7	8	9	10	11	12		
Cell Label	-	1													
Vegetation Type	-->	none													
Inflow Fraction	-	1													
Downstream Cell Number	-	1													
Surface Area	km2	61.54													
Mean Width of Flow Pi	km	6.70													
Number of Tanks in Series	-	1.0													
Minimum Depth for Releases	cm	15													
Release 1 Series Name	-	IRRIG													
Release 2 Series Name	-	TO_A2													
Outflow Series Name	-	TO_STA													
Depth Series Name	-	A1_DEPTH													
Outflow Control Depth	cm	100													
Outflow Weir Depth	cm	100													
Outflow Coefficient - Exponent	-	1.5													
Outflow Coefficient - Intercept	-	8													
Bypass Depth	cm	100													
Maximum Inflow	hm3/day	9.05233													
Maximum Outflow	hm3/day	9.05233													
Inflow Seepage Rate	(cm/d) / cm	3													
Inflow Seepage Control Elev	cm	100													
Inflow Seepage Conc	ppb	10													
Outflow Seepage Rate	(cm/d) / cm	0.00081													
Outflow Seepage Control Elev	cm	6													
Max Outflow Seepage Conc	ppb	100													
Seepage Recycle to Cell Number	-	1													
Seepage Recycle Fraction	-	0.75													
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	105													
Initial P Storage Per Unit Area	mg/m2	525													
Initial Water Column Depth	cm	150													
C0 = Conc at 0 g/m2 P Storage	ppb	3													
C1 = Conc at 1 g/m2 P storage	ppb	150													
C2 = Conc at Half-Max Uptake	ppb	150													
K = Net Settling Rate at Steady State	m/yr	9.0													
Z1 = Saturated Uptake Depth	cm	40													
Z2 = Lower Penalty Depth	cm	100													
Z3 = Upper Penalty Depth	cm	400													
Output Variables			1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.33													1.33
Run Date	-	10/13/06													10/13/06
Starting Date for Simulation	-	01/01/65													01/01/65
Starting Date for Output	-	05/01/65													05/01/65
Ending Date	-	04/30/00													04/30/00
Output Duration	days	12784													12784
Cell Label	-	1													Total
Downstream Cell Label	-	Outflow													-
Network Simulation Name	-	EAASR_NET													EAASR_NET
Simulation Type	-	Base													Base
Surface Area	km2	61.54													61.54
Mean Rainfall	cm/yr	130.73													130.73
Mean ET	cm/yr	135.34													135.34
Cell Inflow Volume	hm3/yr	717.8													717.8
Cell Inflow Load	kg/yr	87205.1													87205.1
Cell Inflow Conc	ppb	121													121
Treated Outflow Volume	hm3/yr	578.3													578.3
Treated Outflow Load	kg/yr	55795.5													55795.5
Treated FWM Outflow Conc	ppb	96													96
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Total Outflow Volume + Bypass	hm3/yr	701.7													701.7
Total Outflow Load + Bypass	kg/yr	68849.9													68849.9
Total FWM Outflow Conc	ppb	98.1													98.1
Bypass Load	kg/yr	0													0
Bypass Load %	%	0%													0
Maximum Inflow	hm3/d	4.33													4.33
Maximum Outflow	hm3/d	3.99													3.99
Surface Load Reduction	kg/yr	31410													31410
Load Trapped in Sediments	kg/yr	18519													18519
Overall Load Reduction	%	21%													21%
Lower Confidence Limit	%	#N/A													#N/A
Upper Confidence Limit	%	#N/A													#N/A
Daily Geometric Mean	ppb	69.0													#N/A
Outflow Geo Mean - Composites	ppb	76.1													76.1
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Frequency Outflow Conc > 10 ppb	%	100%													100%
Frequency Outflow Conc > 20 ppb	%	100%													100%
Frequency Outflow Conc > 50 ppb	%	83%													100%
Freq Outflow Volume > 10 ppb	%	82%													82%
95th Percentile Outflow Conc	ppb	130.61													131
Mean Biomass P Storage	mg/m2	493													493
Storage Increase / Net Removal	%	1%													1%
Net Storage Turnover Rate	1/yr	21.4													21.4
Unit Area P Load	mg/m2-yr	1417													1417
Unit Area P Removal	mg/m2-yr	301													301
Mean Water Load	cm/d	3.2													3.2
Max Water Load	cm/d	7.0													7.0
Mean Depth	cm	222													222
Minimum Depth	cm	31.3													31
Maximum Depth	cm	365.4													365
Frequency Depth < 10 cm	%	0%													0.0%
Flow/Width	m2/day	293													293.3
HRT Days	days	69.8													69.8
Mean Velocity	cm/sec	0.15													0.15
Seepage Outflow / Total Outflow	%	1%													2%
Release 1 Outflow Volume	hm3/yr	0.00													0.0
Release 2 Outflow Volume	hm3/yr	123.43													123.4
95th Percentile Outflow Volume	hm3/d	3.2													3.2
95th Percentile Outflow Load	kg/d	404.0													404.0
Simulated / Specified Mean Depth	%	99%													1.0
Release 1 Demand Met	%	#N/A													#N/A
Release 2 Demand Met	%	98%													1.0
Outflow Demand Met	%	101%													1.0
Range Check - Mean Depth	-														0
Range Check - Free Depth < 10 cm	-														0
Range Check - Flow/Width	-														0
Range Check - Inflow Conc	-														0
Range Check - Outflow Conc	-														0
Water Balance Error	%	0.00%													0.00%
Mass Balance Error	%	0.00%													0.00%



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	A2	Compartment A-2												
Input Series Name	-	TS_A2	13,775 acres of effective area												
Starting Date for Simulation	-	01/01/65	Inflow volumes, outflow volumes, and depths from SFWMM simulation												
Ending Date for Simulation	-	04/30/00	Tested series compare DMSTA simulation with independent sfwmm simulation												
Starting Date for Output	-	05/01/65													
Integration Steps Per Day	-	4													
Number of Iterations	-	0													
Output Averaging Interval	days	365													
Inflow Conc Scale Factor	-	1													
Rainfall P Conc	ppb	10													
Atmospheric P Load (Dry)	mg/m2-yr	20													
Cell Number -->		1	2	3	4	5	6	7	8	9	10	11	12		
Cell Label	-	RES_A2													
Vegetation Type	-->	none													
Inflow Fraction	-	1													
Downstream Cell Number	-														
Surface Area	km2	55.77													
Mean Width of Flow P	km	10.00													
Number of Tanks in Series	-	1.0													
Minimum Depth for Releases	cm	15													
Release 1 Series Name	-	IRRIG													
Release 2 Series Name	-														
Outflow Series Name	-	TO_A1													
Depth Series Name	-	A2_DEPTH													
Outflow Control Depth	cm														
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	1.5													
Outflow Coefficient - Intercept	-	8													
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day	7.829													
Inflow Seepage Rate	(cm/d) / cm														
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.000778													
Outflow Seepage Control Elev	cm	6													
Max Outflow Seepage Conc	ppb	100													
Seepage Recycle to Cell Number	-	1													
Seepage Recycle Fraction	-	0.75													
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	90													
Initial P Storage Per Unit Area	mg/m2	375													
Initial Water Column Depth	cm	200													
C0 = Conc at 0 g/m2 P Storage	ppb	9													
C1 = Conc at 1 g/m2 P storage	ppb	150													
C2 = Conc at Half-Max Uptake	ppb														
K = Net Settling Rate at Steady State	m/yr	9.0													
Z1 = Saturated Uptake Depth	cm	40													
Z2 = Lower Penalty Depth	cm	100													
Z3 = Upper Penalty Depth	cm	400													
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	1.36													1.36
Run Date	-	10/13/06													10/13/06
Starting Date for Simulation	-	01/01/65													01/01/65
Starting Date for Output	-	05/01/65													05/01/65
Ending Date	-	04/30/00													04/30/00
Output Duration	days	12784													12784
Cell Label	-	RES_A2													Total
Downstream Cell Label	-	Outflow													-
Network Simulation Name	-	EAASR_NET													EAASR_NET
Simulation Type	-	Base													Base
Surface Area	km2	55.77													55.77
Mean Rainfall	cm/yr	128.19													128.2
Mean ET	cm/yr	137.71													137.7
Cell Inflow Volume	hm3/yr	460.7													460.7
Cell Inflow Load	kg/yr	41383.2													41383
Cell Inflow Conc	ppb	90													89.8
Treated Outflow Volume	hm3/yr	232.9													232.9
Treated Outflow Load	kg/yr	14517.4													14517
Treated FWM Outflow Conc	ppb	62													62.3
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Total Outflow Volume + Bypass	hm3/yr	441.8													441.8
Total Outflow Load + Bypass	kg/yr	28757.0													28757.0
Total FWM Outflow Conc	ppb	65.1													65.1
Bypass Load	kg/yr	0													0.0
Bypass Load	%	0%													0.0
Maximum Inflow	hm3/d	1.90													1.90
Maximum Outflow	hm3/d	1.30													1.30
Surface Load Reduction	kg/yr	26866													26866
Load Trapped in Sediments	kg/yr	13277													13277
Overall Load Reduction	%	31%													31%
Lower Confidence Limit	%	#N/A													#N/A
Upper Confidence Limit	%	#N/A													#N/A
Daily Geometric Mean	ppb	66.0													#N/A
Outflow Geo Mean - Composites	ppb	64.6													64.6
Upper Confidence Limit	ppb	#N/A													#N/A
Lower Confidence Limit	ppb	#N/A													#N/A
Frequency Outflow Conc > 10 ppb	%	100%													100%
Frequency Outflow Conc > 20 ppb	%	100%													100%
Frequency Outflow Conc > 50 ppb	%	89%													100%
Freq Outflow Volume > 10 ppb	%	53%													53%
95th Percentile Outflow Conc	ppb	86.41													86
Mean Biomass P Storage	mg/m2	409													409
Storage Increase / Net Removal	%	1%													1%
Net Storage Turnover Rate	1/yr	20.4													20.4
Unit Area P Load	mg/m2-yr	742													742
Unit Area P Removal	mg/m2-yr	238													238
Mean Water Load	cm/d	2.3													2.3
Max Water Load	cm/d	3.4													3.4
Mean Depth	cm	260													260
Minimum Depth	cm	50.9													51
Maximum Depth	cm	391.6													392
Frequency Depth < 10 cm	%	0%													0.0%
Flow/Width	m2/day	126													126.1
HRT Days	days	115.1													115.1
Mean Velocity	cm/sec	0.06													0.06
Seepage Outflow / Total Outflow	%	2%													4%
Release 1 Outflow Volume	hm3/yr	208.92													208.9
Release 2 Outflow Volume	hm3/yr	0.00													0.0
95th Percentile Outflow Volume	hm3/d	1.2													1.2
95th Percentile Outflow Load	kg/d	68.2													68.2
Simulated / Specified Mean Depth	%	99%													1.0
Release 1 Demand Met	%	97%													1.0
Release 2 Demand Met	%	#N/A													#N/A
Outflow Demand Met	%	101%													1.0
Range Check - Mean Depth	-														0
Range Check - Free Depth < 10 cm	-														0
Range Check - Flow/Width	-														0
Range Check - Inflow Conc	-														0
Range Check - Outflow Conc	-														0
Water Balance Error	%	0.00%													0.00%
Mass Balance Error	%	0.00%													0.00%



Final Draft - EAASR STA Preliminary Sizing Analysis

Input Variable	Units	Value	Case Description:												
Design Case Name	-	STAS4	STA-3/4 and the new EAASR STA												
Input Series Name	-	TS_3/4/34	Inflows distributed uniformly based on area												
Starting Date for Simulation	-	01/01/65	New STA hydraulics based on average of existing STA-3/4 hydraulics												
Ending Date for Simulation	-	04/30/00	Lake Okechobee deliveries at 150 ppb												
Starting Date for Output	-	05/01/65	The effective treatment area of the new STA, in acres, is estimated at 14,640												
Integration Steps Per Day	-	4													
Number of Iterations	-	3													
Output Averaging Interval	days	365													
Inflow Conc. Scale Factor	-	1													
Rainfall P Conc	ppb	10													
Atmospheric P Load (Dry)	mg/m2-yr	20													
Cell Number ->			1	2	3	4	5	6	7	8	9	10	11	12	
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	
Vegetation Type	->		EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	EMG_3	SAV_3	
Inflow Fraction	-	0.211928652	0.176512247	0.148678	0.148678	0.148678	0.148678	0.148678	0.148678	0.148678	0.148678	0.148678	0.148678	0.148678	
Downstream Cell Number	-	2	4	6	8	10	12	14	16	18	20	22	24	26	
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	7.69	11.54	7.69	11.54	7.69	11.54	7.69	
Mean Width of Flow Path	km	3.42	4.50	2.89	4.02	4.88	4.88	3.33	3.33	3.33	3.33	3.33	3.33	3.33	
Number of Tanks in Series	-	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	
Minimum Depth for Releases	cm														
Release 1 Series Name	-														
Release 2 Series Name	-														
Outflow Series Name	-														
Depth Series Name	-														
Outflow Control Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	
Outflow Weir Depth	cm														
Outflow Coefficient - Exponent	-	4	4	4	4	4	4	4	4	4	4	4	4	4	
Outflow Coefficient - Intercept	-	1	1	1	1	1	1	1	1	1	1	1	1	1	
Bypass Depth	cm														
Maximum Inflow	hm3/day														
Maximum Outflow	hm3/day														
Inflow Seepage Rate	(cm/d) / cm	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	12784	
Inflow Seepage Control Elev	cm														
Inflow Seepage Conc	ppb														
Outflow Seepage Rate	(cm/d) / cm	0.0058	0.0029	0.0014		0.0038		0.0035		0.0035		0.0035		0.0035	
Outflow Seepage Control Elev	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	
Max Outflow Seepage Conc	ppb	20	20	20	20	20	20	20	20	20	20	20	20	20	
Seepage Recycle to Cell Number	-	1	3	5	7	9	11	13	15	17	19	21	23	25	
Seepage Recycle Fraction	-	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Seepage Discharge Fraction	-														
Initial Water Column Conc	ppb	52	12	55	15	55	15	55	15	55	15	55	15	55	
Initial P Storage Per Unit Area	mg/m2	2400	615	2400	615	2400	615	2400	615	2400	615	2400	615	2400	
Initial Water Column Depth	cm	60	60	60	60	60	60	60	60	60	60	60	60	60	
C0 = Conc at 0 gm2 P Storage	ppb	3	3	3	3	3	3	3	3	3	3	3	3	3	
C1 = Conc at 1 gm2 P Storage	ppb	22	22	22	22	22	22	22	22	22	22	22	22	22	
C2 = Conc at Half-Max Uptake	ppb	300	300	300	300	300	300	300	300	300	300	300	300	300	
K = Net Settling Rate at Steady State	m/yr	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	52.5	16.8	
Z1 = Saturated Uptake Depth	cm	40	40	40	40	40	40	40	40	40	40	40	40	40	
Z2 = Lower Penalty Depth	cm	100	100	100	100	100	100	100	100	100	100	100	100	100	
Z3 = Upper Penalty Depth	cm	200	200	200	200	200	200	200	200	200	200	200	200	200	
Output Variables	Units		1	2	3	4	5	6	7	8	9	10	11	12	Overall
Execution Time	sec/yr	29.81	31.16	32.58	33.71	35.30	37.48	38.83	40.76	41.35	42.60	43.87	45.26	45.26	101/306
Run Date	-	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06	10/13/06
Starting Date for Simulation	-	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65	01/01/65
Ending Date for Simulation	-	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65	05/01/65
Ending Date	-	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00	04/30/00
Output Duration	days														
Cell Label			1A	1B	2A	2B	3A	3B	4A	4B	5A	5B	6A	6B	Total
Downstream Cell Label			1B	Outflow	2B	Outflow	3B	Outflow	4B	Outflow	5B	Outflow	6B	Outflow	Outflow
Network Simulation Name	-	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET	EAASR_NET
Simulation Type	-	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base	Base
Surface Area	km2	12.30	14.12	10.29	11.71	9.61	8.92	7.69	11.54	7.69	11.54	7.69	11.54	7.69	124.63
Mean Rainfall	cm/yr	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	129.99	130.0
Mean ET	cm/yr	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.17	134.2
Cell Inflow Volume	hm3/yr	182.8	182.8	182.8	182.8	182.8	182.8	182.8	182.8	182.8	182.8	182.8	182.8	182.8	908.6
Cell Inflow Load	kg/yr	18674.7	9703.1	15553.9	8148.8	13101.2	6178.2	13596.7	7771.4	13596.7	7771.4	13596.7	7771.4	13596.7	88120
Cell Inflow Conc	ppb	97	52	97	52	97	49	97	57	97	57	97	57	97	97.0
Treated Outflow Volume	hm3/yr	186.9	186.2	156.7	156.2	127.3	126.9	137.3	136.8	137.3	136.8	137.3	136.8	137.3	878.7
Treated FWM Outflow Conc	kg/yr	9703.1	2163.0	8148.8	1863.1	6178.2	1563.1	7771.4	1573.6	7771.4	1573.6	7771.4	1573.6	7771.4	10350
Upper Confidence Limit	ppb	12	12	12	12	12	12	12	12	12	12	12	12	12	11.8
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Total Outflow Volume + Bypass	hm3/yr	186.9	186.2	156.7	156.2	127.3	126.9	137.3	136.8	137.3	136.8	137.3	136.8	137.3	878.7
Total Outflow Load + Bypass	kg/yr	9703.1	2163.0	8148.8	1863.1	6178.2	1563.1	7771.4	1573.6	7771.4	1573.6	7771.4	1573.6	7771.4	10350
Total FWM Outflow Conc	ppb	51.9	11.8	52.0	11.9	48.5	12.5	56.6	11.5	56.6	11.5	56.6	11.5	56.6	11.8
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Bypass Load	kg/yr	0	0	0	0	0	0	0	0	0	0	0	0	0	0.0
Maximum Inflow	hm3/d	1.01	1.00	0.84	0.84	0.71	0.69	0.73	0.73	0.73	0.73	0.73	0.73	0.73	4.75
Maximum Outflow	hm3/d	1.00	1.00	0.84	0.84	0.69	0.69	0.73	0.73	0.73	0.73	0.73	0.73	0.73	4.75
Surface Load Reduction	kg/yr	8972	7520	7405	6286	6923	4595	5825	6198	5825	6198	5825	6198	5825	77730
Load Trapped in Sediments	kg/yr	8909	7970	7464	6679	6539	4895	5841	6584	5841	6584	5841	6584	5841	79732
Overall Load Reduction	%	48%	78%	42%	77%	53%	74%	43%	80%	43%	80%	43%	80%	43%	58%
Lower Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Upper Confidence Limit	%	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Daily Geometric Mean	ppb	44.2	7.8	44.5	7.9	43.8	8.0	48.4	7.6	48.4	7.6	48.4	7.6	48.4	#N/A
Outflow Geo Mean - Composites	ppb	46.1	10.0	46.2	10.1	43.2	10.8	50.3	9.8	50.3	9.8	50.3	9.8	50.3	10.0
Upper Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Lower Confidence Limit	ppb	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A	#N/A
Frequency Outflow Conc > 10 ppb	%	100%	50%	100%	53%	100%	58%	100%	50%	100%	50%	100%	50%	100%	50%
Frequency Outflow Conc > 20 ppb	%	100%	0%	100%	0%	100%	0%	100%	0%	100%	0%	100%	0%	100%	8%
Frequency Outflow Conc > 50 ppb	%	50%	0%	50%	0%	44%	0%	56%	0%	56%	0%	56%	0%	56%	0%
Freq Outflow Volume > 10 ppb	%	100%	64%	100%	65%	100%	70%	100%	62%	100%	62%	100%	62%	100%	64%
95th Percentile Outflow Conc	ppb	69.59	15.65	69.74	15.86	64.66	16.36	75.94	14.99	75.94	14.99	75.94	14.99	75.94	15
Mean Biomass P Storage	mg/m2	2297	579	2301	585	2169	564	2406	585	2406	585	2406	585	2406	1352
Storage Increase / Net Removal	-</														